AIR FLOW SENSOR CLEANER BARDAHL

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Reference number: 3259
Issue date: 08-11-17 Revision date: 15-10-21 Supersedes version of: 13-09-19 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : AIR FLOW SENSOR CLEANER BARDAHL
Product code : 3259 # 739235R2
Type of product : Detergent,aerosol
Vaporizer : aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Consumer use
Function or use category : Cleaning/washing agents and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Distributor
SADAPS BARDAHL Additives & Lubricants
ZI TOURNAI OUEST 2 - RUE DU MONT DES CARLIERS, 3
7522 TOURNAI
BELGIQUE
T +32 (0).69.59.03.60 - F +32 (0).69.59.03.61
msds@bardahlfrance.com - www.bardahl.fr

Supplier
SADAPS BARDAHL Additives & Lubricants
ZI TOURNAI OUEST 2 - RUE DU MONT DES CARLIERS, 3
7522 TOURNAI
BELGIQUE
T +32 (0).69.59.03.60 - F +32 (0).69.59.03.61
msds@bardahlfrance.com - www.bardahl.fr

1.4. Emergency telephone number

Emergency number : + 32 (0)70.245.245 / +33 (0)1.45.42.59.59

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals-24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital MSD 2090 Msida	+356 2545 6508	
Saudi Arabia	Poison Control Center-Riyadh	General Directorate of Health Affairs Medial Province	+966 112324180 +966 112324189	
United Arab Emirates	Health Authority – Abu Dhabi (HAAD) Poison & Drug Information Center (PDIC)	P.O. Box 5674 Abu Dhabi	+ 800-424	
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	+44 20 7188 7188	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1	H222;H229
Skin corrosion/irritation, Category 2	H315
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336
Aspiration hazard, Category 1	H304
Hazardous to the aquatic environment — Chronic Hazard, Category 2	H411

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02 GHS07 GHS09

Signal word (CLP) : Danger

Contains : Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Hazard statements (CLP) : H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H315 - Causes skin irritation.
H336 - May cause drowsiness or dizziness.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) : P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P260 - Do not breathe gas, vapours.
P264 - Wash hands thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear protective gloves.
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER, a doctor.
P312 - Call a POISON CENTER, doctor if you feel unwell.
P391 - Collect spillage.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P501 - Dispose of contents/container to a hazardous or special waste collection point.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122 °F.

Extra phrases : Use as per instructions and specifically for this purpose.

Child-resistant fastening : Not applicable

Tactile warning : Not applicable

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	CAS-No.: 92128-66-0 EC-No.: 921-024-6 REACH-no: 01-2119475514-35	>50	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
butane (<0.1% (203-450-8)) substance with national workplace exposure limit(s) (AT, BE, DE, DK, ES, FI, FR, GB, HU, IE, LV, PL) (Note C)(Note U)	CAS-No.: 106-97-8 EC-No.: 203-448-7 EC Index-No.: 601-004-00-0 REACH-no: 01-2119474691-32	20-50	Flam. Gas 1A, H220 Press. Gas

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
Note U (Table 3): When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.
Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.
Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If medical advice is needed, have product container or label at hand.

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

First-aid measures after skin contact : Remove contaminated clothes. Wash skin with plenty of water. Wash contaminated clothing before reuse.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

First-aid measures after ingestion : Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Shortness of breath. May cause respiratory irritation. May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Causes skin irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Water spray. Dry powder. Foam. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

Hazardous decomposition products in case of fire : Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

5.3. Advice for firefighters

Firefighting instructions	:	Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers. Prevent fire fighting water from entering the environment. DO NOT fight fire when fire reaches explosives. Evacuate area.
Protection during firefighting	:	Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	:	Prevent liquid from entering sewers, watercourses, underground or low areas.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	:	Evacuate area. Eliminate every possible source of ignition. Ensure adequate ventilation, especially in confined areas. Keep public away from danger area. Equip cleanup crew with proper protection.

6.1.1. For non-emergency personnel

Emergency procedures	:	Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment	:	Equip cleanup crew with proper protection.
Emergency procedures	:	Ventilate area.

6.2. Environmental precautions

Dike for recovery or absorb with appropriate material. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	:	Recover the product with absorbent material.
Methods for cleaning up	:	Clean up any spills as soon as possible, using an absorbent material to collect it. Store away from other materials.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	:	Do not eat, drink or smoke when using this product. Provide good ventilation in process area to prevent formation of vapour. For further information refer to section 8: "Exposure controls/personal protection". Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.
Hygiene measures	:	Wash contaminated clothing before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	:	Provide local exhaust or general room ventilation.
Storage conditions	:	Keep only in the original container in a cool, well ventilated place away from : Heat sources. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep container tightly closed.
Incompatible products	:	Strong bases. Strong acids.
Incompatible materials	:	Sources of ignition. Direct sunlight. Heat sources.
Heat and ignition sources	:	Keep away from naked flames/heat. Keep away from ignition sources. Do not expose to temperatures exceeding 50 °C/ 122 °F.
Information on mixed storage	:	Keep away from food, drink and animal feeding stuffs.
Storage area	:	Store in a well-ventilated place. Store in a dry place.
Special rules on packaging	:	Store in original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

butane (<0.1% (203-450-8)) (106-97-8)	
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	1600 mg/m³
MAK (OEL TWA) [ppm]	800 ppm
MAK (OEL STEL)	3800 mg/m³
MAK (OEL STEL) [ppm]	1600 ppm
Belgium - Occupational Exposure Limits	
OEL STEL	2370 mg/m³
OEL STEL [ppm]	980 ppm
Denmark - Occupational Exposure Limits	
OEL TWA [1]	1200 mg/m³
OEL TWA [2]	500 ppm
OEL STEL	2400 mg/m³
OEL STEL [ppm]	1000 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA) [1]	1900 mg/m³
HTP (OEL TWA) [2]	800 ppm
HTP (OEL STEL)	2400 mg/m³
HTP (OEL STEL) [ppm]	1000 ppm
France - Occupational Exposure Limits	
Local name	n-Butane
VME (OEL TWA)	1900 mg/m³
VME (OEL TWA) [ppm]	800 ppm
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	2400 mg/m³
AGW (OEL TWA) [2]	1000 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	2350 mg/m³
CK (OEL STEL)	9400 mg/m³
Ireland - Occupational Exposure Limits	
OEL STEL [ppm]	1000 ppm
Latvia - Occupational Exposure Limits	
OEL TWA	300 mg/m³

butane (<0.1% (203-450-8)) (106-97-8)	
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	1900 mg/m³
NDSCh (OEL STEL)	3000 mg/m³
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [1]	1935 mg/m³
VLA-ED (OEL TWA) [2]	800 ppm
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	1450 mg/m³
WEL TWA (OEL TWA) [2]	600 ppm
WEL STEL (OEL STEL)	1810 mg/m³
WEL STEL (OEL STEL) [ppm]	750 ppm
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA) [1]	1900 mg/m³
MAK (OEL TWA) [2]	800 ppm
KZGW (OEL STEL)	7600 mg/m³
KZGW (OEL STEL) [ppm]	3200 ppm
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	1900 mg/m³
ACGIH OEL TWA [ppm]	800 ppm

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:
Safety glasses. EN 166

8.2.2.2. Skin protection

Skin and body protection:
Wear suitable protective clothing

Hand protection:
Gloves. EN 374

8.2.2.3. Respiratory protection

Respiratory protection:
Good ventilation of the workplace required. Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Colour	:	Colourless.
Odour	:	characteristic.
Odour threshold	:	No data available
pH	:	No data available
Relative evaporation rate (butylacetate=1)	:	No data available
Melting point	:	No data available
Freezing point	:	No data available
Boiling point	:	48 °C
Flash point	:	< 0 °C
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Flammability (solid, gas)	:	Extremely flammable aerosol.
Vapour pressure	:	No data available
Relative vapour density at 20 °C	:	No data available
Relative density	:	0,695
Solubility	:	No data available
Partition coefficient n-octanol/water (Log Pow)	:	No data available
Viscosity, kinematic	:	No data available
Viscosity, dynamic	:	No data available
Explosive properties	:	No data available
Oxidising properties	:	No data available
Explosive limits	:	No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Heat. Open flame. Sparks. Direct sunlight. Extremely high or low temperatures. Overheating.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases. fume.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane (92128-66-0)	
LD50 oral rat	> 5840 mg/kg
LD50 dermal rat	> 2920 mg/kg
LC50 Inhalation - Rat	> 25200 mg/m³

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : May cause drowsiness or dizziness.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane (92128-66-0)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified
Aspiration hazard : May be fatal if swallowed and enters airways.

AIR FLOW SENSOR CLEANER BARDAHL	
Vaporizer	aerosol

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane (92128-66-0)	
LC50 - Fish [1]	11,4 mg/l
EC50 - Crustacea [1]	3 mg/l

12.2. Persistence and degradability

AIR FLOW SENSOR CLEANER BARDAHL	
Persistence and degradability	May cause long-term adverse effects in the environment.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane (92128-66-0)	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane (92128-66-0)	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Sewage disposal recommendations : Do not discharge into drains or the environment.

Product/Packaging disposal recommendations : Collect all waste in suitable and labelled containers and dispose according to local legislation. Dispose used or damaged aerosol cans at permitted disposal sites. Do not pierce or burn, even after use.

Additional information : Empty the packaging completely prior to disposal. Do not re-use empty containers.

Ecology - waste materials : Do not discharge the product into the environment.

European List of Waste (LoW) code : 16 05 04* - gases in pressure containers (including halons) containing dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID

ADR	IMDG	IATA	RID
14.1. UN number			
UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name			
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS
Transport document description			
UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1950 Aerosols, flammable, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)			
2.1	2.1	2.1	2.1
			
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable

ADR	IMDG	IATA	RID
14.5. Environmental hazards			
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available			

14.6. Special precautions for user

Overland transport

Classification code (ADR)	:	5F
Special provisions (ADR)	:	190, 327, 344, 625
Limited quantities (ADR)	:	1l
Excepted quantities (ADR)	:	E0
Packing instructions (ADR)	:	P207
Special packing provisions (ADR)	:	PP87, RR6, L2
Mixed packing provisions (ADR)	:	MP9
Transport category (ADR)	:	2
Special provisions for carriage - Packages (ADR)	:	V14
Special provisions for carriage - Loading, unloading and handling (ADR)	:	CV9, CV12
Special provisions for carriage - Operation (ADR)	:	S2
Tunnel restriction code (ADR)	:	D

Transport by sea

Special provisions (IMDG)	:	63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	:	P207, LP200
Special packing provisions (IMDG)	:	PP87, L2
EmS-No. (Fire)	:	F-D
EmS-No. (Spillage)	:	S-U
Stowage category (IMDG)	:	None
Stowage and handling (IMDG)	:	SW1, SW22
Segregation (IMDG)	:	SG69

Air transport

PCA Excepted quantities (IATA)	:	E0
PCA Limited quantities (IATA)	:	Y203
PCA limited quantity max net quantity (IATA)	:	30kgG
PCA packing instructions (IATA)	:	203
PCA max net quantity (IATA)	:	75kg
CAO packing instructions (IATA)	:	203
CAO max net quantity (IATA)	:	150kg
Special provisions (IATA)	:	A145, A167, A802
ERG code (IATA)	:	10L

Rail transport

Classification code (RID)	:	5F
Special provisions (RID)	:	190, 327, 344, 625
Limited quantities (RID)	:	1L
Excepted quantities (RID)	:	E0
Packing instructions (RID)	:	P207, LP200
Special packing provisions (RID)	:	PP87, RR6, L2
Mixed packing provisions (RID)	:	MP9
Transport category (RID)	:	2
Special provisions for carriage – Packages (RID)	:	W14
Special provisions for carriage - Loading, unloading and handling (RID)	:	CW9, CW12
Colis express (express parcels) (RID)	:	CE2
Hazard identification number (RID)	:	23

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions
Contains no substance on the REACH candidate list
Contains no REACH Annex XIV substances
Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.
Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants
Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

Detergent Regulation (648/2004/EC): Labelling of contents:	
Component	**%**
aliphatic hydrocarbons	≥30%

Directive 2012/18/EU (SEVESO III)

Seveso III Part II (Named dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
18. Liquefied flammable gases, Category 1 or 2 (including LPG) and natural gas	50	200

15.1.2. National regulations

Germany

Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG)
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG)

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed

SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed

SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

Switzerland

Storage class (LK) : LK 2 - Liquefied or pressurized gases

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Indication of changes			
Section	**Changed item**	**Change**	**Comments**
1	Product code	Modified	

Indication of changes			
Section	**Changed item**	**Change**	**Comments**
3.2	Composition/information on ingredients	Modified	

Full text of H- and EUH-statements:	
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 2	Flammable liquids, Category 2
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
Press. Gas	Gases under pressure
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.