XTEC 0W30 ST

DESCRIPTION

BARDAHL XTEC 0W30 ST is a fully synthetic, next-generation engine oil designed to meet the requirements of Euro 6 petrol and diesel engines, especially those equipped with after-treatment systems such as diesel particulate filters (DPF) and selective catalytic reduction (SCR) catalysts. It is particularly suitable for vehicles from the Stellantis group (Peugeot, Citroën, DS, Fiat, Opel), as well as certain models from Ford, Toyota, and Hyundai/Kia requiring an ACEA C2-compliant lubricant.

PROPERTIES

Thanks to its 0W30 viscosity grade and Low SAPS formulation, **BARDAHL XTEC 0W30 ST** offers:

- Excellent engine protection during cold starts,
- Reduced fuel consumption,
- Lower CO_2 emissions,
- Enhanced durability of emission control systems.

SPECIFICATIONS

The product meets the following requirements:

ACEA	C2
PSA	B71 2312
FCA	9.55535-DS1 / 9.55535-DH1
TOYOTA/HONDA/HYUNDAI/KIA	Selon recommandations constructeurs

SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers,3, ZI Tournai Ouest II
T: (+32) (0) 69 59 03 60
www.bardahl.be
www.bardahloils.com

TECHNICAL DATA

Properties	Method	Unit	Typical value
Appearance	-	-	Clear & translucent
Density, 15°C	ASTM D 4052	g/ml	0.846
Viscosity, 100°C	ASTM D 445	mm²/s	9.45
Viscosity index	ASTM D 2270	-	194
Drop point	ASTM D 97	°C	-50
Flash point (COC)	ASTM D 92	°C	216
Total Base Number (TBN)	ASTM D2896	mg KOH/g	7

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet. Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABITIES

35633	3 x 5L
35637	205L

SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers,3, ZI Tournai Ouest II
T: (+32) (0) 69 59 03 60
www.bardahl.be
www.bardahloils.com