TECHNICAL DATA SHEET
V092026

XTC 5W40

DESCRIPTION

High performance synthetic oil for petrol and diesel engines dated from 2000 and later. It is suitable for turbo-charged or not, multivalve and diesel direct injection engines.

APPLICATION

BARDAHL XTC 5w40 can be used all year long and in the most difficult operating conditions. It is compatible with catalytic converters and recommended for diesel direct injection (TDI, Common rail, HDI). **Approved by Mercedes-Benz.**

SPECIFICATIONS

This product offers the following performance level:

ACEA	A3 / B4
API	SP / CF
VW	502.00 / 505.00
MB	229.5/229.3
Porsche	A40
BMW	Longlife-01
GM	LL-B-025
PSA	B71 2296
RENAULT	RN0700/RN0710
VOLVO	95200356

PROPERTIES

- ✓ Offers a stable viscosity
- ✓ Provides an excellent resistance against shearing
- ✓ Makes cold starting easier
- ✓ Offers a good resistance against oxidation and wear

SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers,3, ZI Tournai Ouest II
T: (+32) (0) 69 59 03 60
www.bardahl.be
www.bardahloils.com

TECHNICAL DATA

Density at 15°C	Kg/l	0,853
Viscosity at -30°C	mPa.s	6030
Viscosity at 40°C	mm2/s	86.90
Viscosity at 100°C	mm2/s	14.50
Viscosity index		174
Flash point COC, °C	°C	231
Pour point, °C	°C	-42
TBN	mgKOH/g	10,4
Sulfated ash contents	%	1,3
HTHS (CEC-L-36-A-90)		3.51

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur
without prior notice. No liability for damages caused by incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling: any safety information related to the handling and use of this product are gathered in the Safety Data Sheet. Always check the manufacturer car manual before use.

Storage: it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36161	12 x 1 L
36162	4 x 4 L
36163	3 x 5 L
36168	20 L
36164	60 L
36167	205 L

SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers,3, ZI Tournai Ouest II
T: (+32) (0) 69 59 03 60
www.bardahl.be
www.bardahloils.com