DECRISTALLISANT ADBLUE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Reference number: 3146B
Issue date: 19-05-26 Revision date: 19-05-26 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : DECRISTALLISANT ADBLUE
UFI : X5QW-5709-3K9H-PT2S
Product code : 3146B # 736314BR0

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Consumer use
Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Distributor
SADAPS BARDAHL Additives & Lubricants
ZI TOURNAI OUEST 2 - RUE DU MONT DES CARLIERS, 3
7522 TOURNAI
BELGIQUE
T +32 (0).69.59.03.60, F +32 (0).69.59.03.61
msds@bardahlfrance.com, www.bardahl.be

Supplier
SADAPS BARDAHL Additives & Lubricants
ZI TOURNAI OUEST 2 - RUE DU MONT DES CARLIERS, 3
7522 TOURNAI
BELGIQUE
T +32 (0).69.59.03.60, F +32 (0).69.59.03.61
msds@bardahlfrance.com, www.bardahl.be

1.4. Emergency telephone number

Emergency number : + 32 (0)70.245.245 / +33 (0)1.45.42.59.59

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals-24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital Msida MSD 2090 Msida	112 +356 2545 6508	
Saudi Arabia	Poison Control Center-Riyadh	General Directorate of Health Affairs Medial Province	+966 112324180 +966 112324189	
United Arab Emirates	Health Authority – Abu Dhabi (HAAD) Poison & Drug Information Center (PDIC)	P.O. Box 5674	+ 800-424	
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER	+44 20 7188 7188	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Corrosive to metals Not classified
Specific target organ toxicity – Repeated exposure, Category 2 H373
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS08

Signal word (CLP) : Warning
Contains : ethylene glycol
Hazard statements (CLP) : H373 - May cause damage to organs (kidneys) through prolonged or repeated exposure.
Precautionary statements (CLP) : P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P260 - Do not breathe vapours.
P280 - Wear protective gloves.
P312 - Call a POISON CENTER, doctor if you feel unwell.
P501 - Dispose of contents/container to a hazardous or special waste collection point.
EUH-statements : EUH208 - Contains Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.
Child-resistant fastening : Not applicable
Tactile warning : Applicable

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

Component	
Sodium hydroxide (1310-73-2)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Component	
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (55965-84-9)	The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ethylene glycol substance with national workplace exposure limit(s) (BE, FI, FR, IT, NL, RO, SE); substance with a Community workplace exposure limit	CAS-No.: 107-21-1 EC-No.: 203-473-3 EC Index-No.: 603-027-00-1 REACH-no: 01-2119456816-28	10-15	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) STOT RE 2, H373
(2-methoxymethylethoxy)propanol substance with national workplace exposure limit(s) (AT, BE, DE, DK, ES, FI, FR, GB, HU, IE, IT, LV, NL, PL, RO, SE); substance with a Community workplace exposure limit	CAS-No.: 34590-94-8 EC-No.: 252-104-2 REACH-no: 01-2119450011-60	<3	Not classified
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) substance with national workplace exposure limit(s) (DE)	CAS-No.: 55965-84-9 EC Index-No.: 613-167-00-5	<0,01	Acute Tox. 3 (Oral), H301 (ATE=66 mg/kg) Acute Tox. 2 (Dermal), H310 (ATE=141 mg/kg bodyweight) Acute Tox. 2 (Inhalation), H330 (ATE=0,17 mg/l/4h) Acute Tox. 2 (Inhalation:dust,mist), H330 (ATE=0,17 mg/l/4h) Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100) EUH071

Specific concentration limits:		
Name	**Product identifier**	**Specific concentration limits**
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1)	CAS-No.: 55965-84-9 EC Index-No.: 613-167-00-5	(0,0015 ≤ C < 100) Skin Sens. 1A; H317 (0,06 ≤ C < 0,6) Eye Irrit. 2; H319 (0,06 ≤ C < 0,6) Skin Irrit. 2; H315 (0,6 ≤ C < 100) Skin Corr. 1C; H314 (0,6 ≤ C < 100) Eye Dam. 1; H318

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If medical advice is needed, have product container or label at hand.

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

First-aid measures after skin contact : Remove contaminated clothes. Wash skin with plenty of water. Wash contaminated clothing before reuse.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

First-aid measures after ingestion : Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May produce an allergic reaction. May cause damage to organs (kidneys) through prolonged or repeated exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Water spray. Dry powder. Foam.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.
Other information : Prevent liquid from entering sewers, watercourses, underground or low areas.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area. Eliminate every possible source of ignition. Ensure adequate ventilation, especially in confined areas. Keep public away from danger area. Equip cleanup crew with proper protection.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Dike for recovery or absorb with appropriate material. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Recover the product with absorbent material.
Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not eat, drink or smoke when using this product.
Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Provide local exhaust or general room ventilation.
Storage conditions : Store in a closed container. Keep out of frost.
Heat and ignition sources : Keep away from naked flames/heat. Keep away from ignition sources.
Storage area : Store in a dry place. Store in a well-ventilated place.

Special rules on packaging : Store in original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

ethylene glycol (107-21-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Ethylene glycol
IOEL TWA	52 mg/m³
	20 ppm
IOEL STEL	104 mg/m³
	40 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Belgium - Occupational Exposure Limits	
Local name	Ethylèneglycol (en aérosol) # Ethyleenglycol
OEL TWA	52 mg/m³
	20 ppm
OEL STEL	104 mg/m³
	40 ppm
Remark	D: la mention “D” signifie que la résorption de l’agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l’exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l’agent dans l’air, M: la mention “M” indique que lors d’une exposition supérieure à la valeur limite, des irritations apparaissent ou un danger d’intoxication aiguë existe. Le procédé de travail doit être conçu de telle façon que l’exposition ne dépasse jamais la valeur limite. Lors des mesurages, la période d’échantillonnage doit être aussi courte que possible afin de pouvoir effectuer des mesurages fiables. Le résultat des mesurages est calculé en fonction de la période d’échantillonnage. # D: de vermelding “D” betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht, M: de vermelding “M” duidt aan dat bij de blootstelling boven de grenswaarde irritatie optreedt of er gevaar bestaat voor acute vergiftiging. Het werkprocédé moet zo zijn ontworpen dat de blootstelling de grenswaarde nooit overschrijdt. Bij een controle geldt dat de bemonsterde periode zo kort mogelijk moet zijn om een betrouwbare meting te kunnen verrichten. Het meetresultaat wordt dan gerelateerd aan de beschouwde periode.
Regulatory reference	Koninklijk besluit/Arrêté royal 21/01/2020
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	50 mg/m³
	20 ppm
HTP (OEL STEL)	100 mg/m³
	40 ppm

ethylene glycol (107-21-1)	
France - Occupational Exposure Limits	
Local name	Ethylèneglycol (vapeur)
VLEP 8h (OEL TWA)	52 mg/m³
	20 ppm
VLEP CT (OEL STEL)	104 mg/m³
	40 ppm
Remark	Valeurs règlementaires indicatives; risque de pénétration percutanée
Regulatory reference	Arrêté du 30 juin 2004 modifié (réf.: INRS ED 984, 2016)
Italy - Occupational Exposure Limits	
OEL TWA	52 mg/m³
	20 ppm
OEL STEL	104 mg/m³
	40 ppm
Netherlands - Occupational Exposure Limits	
TGG-C (OEL C)	104 mg/m³
	40 ppm
Romania - Occupational Exposure Limits	
OEL TWA	52 mg/m³
	20 ppm
OEL STEL	104 mg/m³
	40 ppm
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	25 mg/m³
	10 ppm
KGV (OEL STEL)	104 mg/m³
	40 ppm

(2-methoxymethylethoxy)propanol (34590-94-8)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	(2-Methoxymethylethoxy)-propanol
IOEL TWA	308
	50 ppm
Remark	Skin
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	307 mg/m³
	50 ppm
MAK (OEL STEL)	614 mg/m³
	100 ppm
Belgium - Occupational Exposure Limits	
OEL TWA	308 mg/m³

(2-methoxymethylethoxy)propanol (34590-94-8)	
	50 ppm
Denmark - Occupational Exposure Limits	
8-timers grænseværdi (OEL TWA)	309 mg/m³
	50 ppm
Korttidsgrænseværdi (OEL STEL)	618 mg/m³
	100 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	310 mg/m³
	50 ppm
France - Occupational Exposure Limits	
Local name	(2-méthoxyméthyléthoxy)-propanol
VLEP 8h (OEL TWA)	308 mg/m³
	50 ppm
Remark	Valeurs règlementaires contraignantes; risque de pénétration percutanée
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	310 mg/m³
	50 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	308 mg/m³
CK (OEL STEL)	308 mg/m³
Ireland - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
Italy - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
Latvia - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	300 mg/m³
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	240 mg/m³
NDSCh (OEL STEL)	280 mg/m³
Romania - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	308 mg/m³

(2-methoxymethylethoxy)propanol (34590-94-8)	
	50 ppm
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	300 mg/m³
	50 ppm
KGV (OEL STEL)	450 mg/m³
	75 ppm
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	308 mg/m³
	50 ppm
WEL STEL (OEL STEL)*	924 mg/m³
	150 ppm
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	300 mg/m³
	50 ppm
KZGW (OEL STEL)	300 mg/m³
	50 ppm
USA - ACGIH® - Threshold Limit Values	
ACGIH® TLV® TWA	600 mg/m³
	100 ppm
ACGIH® TLV® STEL	900 mg/m³
	150 ppm

Sodium hydroxide (1310-73-2)	
France - Occupational Exposure Limits	
VLEP 8h (OEL TWA)	2 mg/m³

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (55965-84-9)	
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	0,2 mg/m³
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	0,2 mg/m³
KZGW (OEL STEL)	0,4 mg/m³

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:
Safety glasses. ISO 16321-1

8.2.2.2. Skin protection

Skin and body protection:
Wear suitable protective clothing

Hand protection:
Gloves. ISO 374-1

8.2.2.3. Respiratory protection

Respiratory protection:
Good ventilation of the workplace required

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Colour	:	Yellow.
Appearance	:	Cloudy.
Odour	:	Not available
Odour threshold	:	Not available
Melting point	:	Not available
Freezing point	:	Not available
Boiling point	:	Not available
Flammability	:	Not available
Explosive limits	:	Not available
Lower explosion limit	:	Not available
Upper explosion limit	:	Not available
Flash point	:	> 60 °C
Auto-ignition temperature	:	Not available
Decomposition temperature	:	Not available
pH	:	7 – 9 (ASTM D1287)
Viscosity, kinematic	:	> 20,5 mm²/s (40°C)
Solubility	:	Not available
Partition coefficient n-octanol/water (Log Kow)	:	Not available
Vapour pressure	:	Not available
Vapour pressure at 50°C	:	Not available
Density	:	1,007 – 1,027 g/cm³ (20°C)
Relative density	:	Not available
Relative vapour density at 20°C	:	Not available

Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Heat. Open flame. Sparks. Water, humidity. Freezing.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

ethylene glycol (107-21-1)	
LD50 oral rat	7712 mg/kg bodyweight
LD50 oral	1600 mg/kg
LD50 dermal rat	> 3500 mg/kg bodyweight
LC50 Inhalation - Rat	> 2,5 mg/l

trisodium 5-hydroxy-1-(4-sulphophenyl)-4-(4-sulphophenylazo)pyrazole-3-carboxylate (1934-21-0)	
LD50 oral rat	> 2000 mg/kg

Alcohols, secondary C11-15, ethoxylated (68131-40-8)	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

(2-methoxymethylethoxy)propanol (34590-94-8)	
LD50 oral rat	8740 mg/kg
LD50 dermal rabbit	9510 mg/kg

(2-methoxymethylethoxy)propanol (34590-94-8)	
LC50 Inhalation - Rat	3404,47 mg/l

Sodium hydroxide (1310-73-2)	
LD50 oral	> 500 mg/kg

Skin corrosion/irritation : Not classified
pH: 7 – 9 (ASTM D1287)

Sodium hydroxide (1310-73-2)	
pH	14 10%

Serious eye damage/irritation : Not classified
pH: 7 – 9 (ASTM D1287)

Sodium hydroxide (1310-73-2)	
pH	14 10%

Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

ethylene glycol (107-21-1)	
NOAEL (chronic, oral, animal/male, 2 years)	1000 mg/kg bodyweight
NOAEL (chronic, oral, animal/female, 2 years)	1000 mg/kg bodyweight

Reproductive toxicity : Not classified
STOT-single exposure : Not classified

ethylene glycol (107-21-1)	
NOAEL (oral, rat)	200 mg/kg bodyweight

STOT-repeated exposure : May cause damage to organs (kidneys) through prolonged or repeated exposure.

ethylene glycol (107-21-1)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

DECRISTALLISANT ADBLUE	
Viscosity, kinematic	> 20,5 mm²/s (40°C)

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short–term (acute) : Not classified
Hazardous to the aquatic environment, long–term (chronic) : Not classified

ethylene glycol (107-21-1)	
LC50 - Fish [1]	72860 mg/l (Pimephales promelas)
EC50 - Crustacea [1]	> 100 mg/l (Daphnia magna)
EC50 - Other aquatic organisms [1]	> 6500 mg/l
NOEC chronic fish	15380 mg/l

ethylene glycol (107-21-1)	
NOEC chronic algae	8590 mg/l

(2-methoxymethylethoxy)propanol (34590-94-8)	
LC50 - Fish [1]	> 1000 mg/l Poecilia reticulata (Guppy)
EC50 - Crustacea [1]	1919 mg/l Daphnia magna
ErC50 algae	> 969 mg/l Pseudokirchneriella subcapitata
LOEC (chronic)	0,5 mg/l 22 d, Daphnia magna
NOEC chronic crustacea	0,5 mg/l 22 d, Daphnia magna

Sodium hydroxide (1310-73-2)	
LC50 - Fish [1]	33 – 189 mg/l
EC50 - Crustacea [1]	40 – 240 mg/l

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (55965-84-9)	
LC50 - Fish [1]	0,22 mg/l (Onchorhyncus mykiss - OECD 203)
EC50 - Crustacea [1]	0,1 mg/l (Daphnia Magna - OECD 202)
EC50 - Other aquatic organisms [1]	0,0052 mg/l (Skeletonema costatum) (OECD 201)
EC50 72h - Algae [1]	0,048 mg/l (Pseudokirchneriella subcapitata - OECD 201)
NOEC chronic fish	0,098 mg/l (Onchorhyncus mykiss) (OECD 215)
NOEC chronic crustacea	0,004 mg/l (Daphnia magna) (OECD 211)
NOEC chronic algae	0,0012 mg/l (Pseudokirchneriella subcapitata) (OECD 201)

12.2. Persistence and degradability

ethylene glycol (107-21-1)	
Biodegradation	90 % (OECD 301D method)

(2-methoxymethylethoxy)propanol (34590-94-8)	
Persistence and degradability	Readily biodegradable.
Biodegradation	75 % 28 days

Sodium hydroxide (1310-73-2)	
Persistence and degradability	Not biodegradable.

12.3. Bioaccumulative potential

ethylene glycol (107-21-1)	
Partition coefficient n-octanol/water (Log Kow)	-1,36

(2-methoxymethylethoxy)propanol (34590-94-8)	
Partition coefficient n-octanol/water (Log Pow)	0,006

Sodium hydroxide (1310-73-2)	
Bioaccumulative potential	not bioaccumulable.

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) (55965-84-9)	
Partition coefficient n-octanol/water (Log Kow)	≤ 0,71

12.4. Mobility in soil

(2-methoxymethylethoxy)propanol (34590-94-8)	
Ecology - soil	In water, material soluble.

Sodium hydroxide (1310-73-2)	
Ecology - soil	In water, material soluble.

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Sewage disposal recommendations : Do not discharge into drains or the environment.

Product/Packaging disposal recommendations : Collect all waste in suitable and labelled containers and dispose according to local legislation.

Additional information : Empty the packaging completely prior to disposal. Do not re-use empty containers.

Ecological waste information : Do not discharge the product into the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID

ADR	IMDG	IATA	RID
14.1. UN number or ID number			
Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name			
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea
Not regulated

Air transport
Not regulated

Rail transport
Not regulated

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Not listed on the Ozone Depletion list (Regulation EU 2024/590)
Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

Austria

Ordinance on Flammable Liquids (VbF) : Auto detect

France

Occupational diseases	
Code	Description
RG 65	Eczematiform lesions of allergic mechanism
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG). Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).
Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).
Override matching entry (12. BImSchV) : Is not subject to the Major Accidents Ordinance (12. BImSchV)

Netherlands

SZW List of Carcinogenic Substances : None of the components are listed
SZW List of Mutagenic Substances : None of the components are listed
SZW List of Reprotoxic Substances – Breastfeeding : None of the components are listed
SZW List of Reprotoxic Substances – Fertility : None of the components are listed
SZW List of Reprotoxic Substances – Development : None of the components are listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with it.
If an employee is pregnant or breastfeeding and the person in question uses or is exposed to this product at work, the employer must always carry out a risk assessment of the work. The assessment must both deal with the dangerousness of the impact and its strength and duration. The employer's decision that a pregnant or lactating woman can perform a specific work task must therefore be made in the context of her specific working conditions. See also WEA-Guideline A.1.8-7 on the working environment of pregnant and breastfeeding workers.

Switzerland

Storage class (LK) : LK 6.1 - Toxic materials

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 2 (Dermal)	Acute toxicity (dermal), Category 2
Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 2 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 2
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1

Full text of H- and EUH-statements:	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Met. Corr. Not classified	Corrosive to metals Not classified
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1A	Skin sensitisation, category 1A
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H373	May cause damage to organs (kidneys) through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.
EUH208	Contains Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.