XTM 20W50 MB

DESCRIPTION

Mineral engine oil for passenger cars and delivery vans. Ideal for multi-fleet applications. Compatible with petrol, diesel and LPG cars, turbo-charged or not and equipped or not with a catalytic converter.

APPLICATION

BARDAHL XTM 20w50 MB offers excellent cleaning properties and very good protection against wear thanks to viscosity stabilizing additives. It also provides good anti-rust and anti-corrosion protection.

SPECIFICATIONS

This product offers the following performance level:

API	SN/CF
ACEA	A3/B4
MB	229.1
VW	505.01/505.00

PROPERTIES

- ✓ Avoids deposits on pistons.
- ✓ Provides excellent cleaning properties.
- ✓ Offers anti-corrosion properties,
- ✓ High and stable viscosity index.

SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers,3, ZI Tournai Ouest II
T: (+32) (0) 69 59 03 60
www.bardahl.be
www.bardahloils.com

TECHNICAL DATA

Density at 20°C	Kg/l	0,892
Viscosity at -15°C	cP	8190
Viscosity at 40°C	mm^2/s	164
Viscosity at 100°C	mm^2/s	17,60
Viscosity Index		120
Flash point COC	°C	238
Pour point	°C	-24
TBN	mgKOH/g	10,7

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 36 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

35701	12 x 1 L
35702	4 x 4 L
35703	3 x 5 L

SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers,3, ZI Tournai Ouest II
T: (+32) (0) 69 59 03 60
www.bardahl.be
www.bardahloils.com