CARBURATOR CLEANER BARDAHL

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Reference number: 2806
Issue date: 20-04-26 Revision date: 20-04-26 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : CARBURATOR CLEANER BARDAHL
UFI : UM6P-K22J-9808-WAFD
Product code : 2806 # 736280R0
Type of product : Detergent,Aerosol
Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Consumer use
Function or use category : Cleaning/washing agents and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Distributor
SADAPS BARDAHL Additives & Lubricants
ZI TOURNAI OUEST 2 - RUE DU MONT DES CARLIERS, 3
7522 TOURNAI
BELGIQUE
T +32 (0).69.59.03.60, F +32 (0).69.59.03.61
msds@bardahlfrance.com, www.bardahl.be

Supplier
SADAPS BARDAHL Additives & Lubricants
ZI TOURNAI OUEST 2 - RUE DU MONT DES CARLIERS, 3
7522 TOURNAI
BELGIQUE
T +32 (0).69.59.03.60, F +32 (0).69.59.03.61
msds@bardahlfrance.com, www.bardahl.be

1.4. Emergency telephone number

Emergency number : + 32 (0)70.245.245 / +33 (0)1.45.42.59.59

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals-24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital Msida MSD 2090 Msida	112 +356 2545 6508	
Saudi Arabia	Poison Control Center-Riyadh	General Directorate of Health Affairs Medial Province	+966 112324180 +966 112324189	
United Arab Emirates	Health Authority – Abu Dhabi (HAAD) Poison & Drug Information Center (PDIC)	P.O. Box 5674	+ 800-424	
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER	+44 20 7188 7188	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1	H222;H229
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335
Specific target organ toxicity – Repeated exposure, Category 2	H373
Aspiration hazard, Category 1	H304
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02 GHS07 GHS08

Signal word (CLP) : Danger

Contains : xylene (mixture); Acetone

Hazard statements (CLP) : H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H335 - May cause respiratory irritation.
H336 - May cause drowsiness or dizziness.
H373 - May cause damage to organs through prolonged or repeated exposure.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P260 - Do not breathe gas, mist.
P271 - Use only outdoors or in a well-ventilated area.
P405 - Store locked up.
P501 - Dispose of contents/container to a hazardous or special waste collection point.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122 °F.

Extra phrases : Use as per instructions and specifically for this purpose.

Child-resistant fastening : Not applicable

Tactile warning : Applicable

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
butane substance with national workplace exposure limit(s) (AT, BE, DE, DK, ES, FI, FR, GB, HU, IE, LV, PL) (Note C)(Note U)	CAS-No.: 106-97-8 EC-No.: 203-448-7 EC Index-No.: 601-004-00-0 REACH-no: 01-2119474691-32	36-48	Flam. Gas 1A, H220 Press. Gas (Comp.), H280
acetone; propan-2-one; propanone substance with national workplace exposure limit(s) (AT, BE, DE, DK, ES, FI, FR, GB, HU, IE, IT, LV, NL, PL, RO, SE); substance with a Community workplace exposure limit	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8	24-60	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
Acetone substance with national workplace exposure limit(s) (AT, BE, DE, DK, ES, FI, FR, GB, HU, IE, IT, LV, NL, PL, RO, SE); substance with a Community workplace exposure limit	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8	15-25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
xylene (mixture) substance with national workplace exposure limit(s) (AT, BE, DE, DK, ES, FI, FR, GB, HU, IE, IT, LV, NL, PL, RO, SE); substance with a Community workplace exposure limit	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-2119488216-32	10-20	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg) Acute Tox. 4 (Inhalation), H332 (ATE=11 mg/l) Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Ethylbenzene substance with national workplace exposure limit(s) (AT, BE, DE, DK, ES, FI, FR, GB, HU, IE, IT, LV, NL, PL, RO, SE); substance with a Community workplace exposure limit	CAS-No.: 100-41-4 EC-No.: 202-849-4 EC Index-No.: 601-023-00-4 REACH-no: 01-2119489370-35	4-10	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412

Specific concentration limits:

Name	Product identifier	Specific concentration limits
xylene (mixture)	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-2119488216-32	(10 ≤ C < 100) STOT RE 2; H373

Note C - Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
Note U - When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned:. Press. Gas (Comp.), Press. Gas (Liq.), Press. Gas (Ref. Liq.), Press. Gas (Diss.). Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).
Product subject to CLP Annex I, item 1.1.3.7. The disclosure rules of the components is modified in this case.
Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If medical advice is needed, have product container or label at hand.

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

First-aid measures after skin contact : Remove contaminated clothes. Wash skin with plenty of water. Wash contaminated clothing before reuse.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

First-aid measures after ingestion : Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Water spray. Dry powder. Foam.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. Heating may cause an explosion.

Hazardous decomposition products in case of fire : Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Other information : Prevent liquid from entering sewers, watercourses, underground or low areas.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area. Eliminate every possible source of ignition. Ensure adequate ventilation, especially in confined areas. Keep public away from danger area. Equip cleanup crew with proper protection.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Dike for recovery or absorb with appropriate material. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Recover the product with absorbent material.

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not eat, drink or smoke when using this product. Provide good ventilation in process area to prevent formation of vapour. For further information refer to section 8: "Exposure controls/personal protection". Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.

Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Provide local exhaust or general room ventilation.

Storage conditions : Keep out of frost.

Heat and ignition sources : Keep away from naked flames/heat. Keep away from ignition sources. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Information on mixed storage : Keep away from food, drink and animal feeding stuffs.

Storage area : Store in a well-ventilated place. Store in a dry place.

Special rules on packaging : Store in original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Ethylbenzene (100-41-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Ethylbenzene
IOEL TWA	442 mg/m³
	100 ppm
IOEL STEL	884 mg/m³
	200 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	440 mg/m³
	100 ppm
MAK (OEL STEL)	880 mg/m³
	200 ppm

Ethylbenzene (100-41-4)	
Belgium - Occupational Exposure Limits	
OEL TWA	87 mg/m³
	20 ppm
OEL STEL	551 mg/m³
	125 ppm
Denmark - Occupational Exposure Limits	
8-timers grænseværdi (OEL TWA)	217 mg/m³
	50 ppm
Korttidsgrænseværdi (OEL STEL)	434 mg/m³
	100 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	220 mg/m³
	50 ppm
HTP (OEL STEL)	880 mg/m³
	200 ppm
France - Occupational Exposure Limits	
Local name	Ethylbenzène
VLEP 8h (OEL TWA)	88,4 mg/m³
	20 ppm
VLEP CT (OEL STEL)	442 mg/m³
	100 ppm
Remark	Valeurs règlementaires contraignantes; risque de pénétration percutanée
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487)
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	88 mg/m³
	20 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	442 mg/m³
CK (OEL STEL)	884 mg/m³
Ireland - Occupational Exposure Limits	
OEL TWA	442 mg/m³
	100 ppm
OEL STEL	884 mg/m³
	200 ppm
Italy - Occupational Exposure Limits	
OEL TWA	442 mg/m³
	100 ppm
OEL STEL	884 mg/m³
	200 ppm

Ethylbenzene (100-41-4)	
Latvia - Occupational Exposure Limits	
OEL TWA	442 mg/m³
	100 ppm
OEL STEL	884 mg/m³
	200 ppm
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	215 mg/m³
TGG-15min (OEL STEL)	430 mg/m³
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	200 mg/m³
NDSP (OEL C)	400 mg/m³
Romania - Occupational Exposure Limits	
OEL TWA	442 mg/m³
	100 ppm
OEL STEL	884 mg/m³
	200 ppm
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	441 mg/m³
	100 ppm
VLA-EC (OEL STEL)	884 mg/m³
	200 ppm
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	220 mg/m³
	50 ppm
KGV (OEL STEL)	884 mg/m³
	200 ppm
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	441 mg/m³
	100 ppm
WEL STEL (OEL STEL)	552 mg/m³
	125 ppm
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	435 mg/m³
	100 ppm
KZGW (OEL STEL)	435 mg/m³
	100 ppm
USA - ACGIH® - Threshold Limit Values	
ACGIH® TLV® TWA	435 mg/m³
	100 ppm

xylene (mixture) (1330-20-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	435 mg/m³
	100 ppm
IOEL STEL	870 mg/m³
	200 ppm
Remark	Skin
EU - Binding Occupational Exposure Limit (BOEL)	
Local name	XYLENE
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	221 mg/m³
	50 ppm
MAK (OEL STEL)	442 mg/m³
	100 ppm
Belgium - Occupational Exposure Limits	
OEL TWA	221 mg/m³
	50 ppm
OEL STEL	442 mg/m³
	100 ppm
Denmark - Occupational Exposure Limits	
8-timers grænseværdi (OEL TWA)	109 mg/m³
	25 ppm
Korttidsgrænseværdi (OEL STEL)	218 mg/m³
	50 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	220 mg/m³
	50 ppm
HTP (OEL STEL)	440 mg/m³
	100 ppm
France - Occupational Exposure Limits	
VLEP 8h (OEL TWA)	221 mg/m³
	50 ppm
VLEP CT (OEL STEL)	442 mg/m³
	100 ppm
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	220 mg/m³
	50 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	221 mg/m³
CK (OEL STEL)	442 mg/m³

xylene (mixture) (1330-20-7)	
Ireland - Occupational Exposure Limits	
OEL TWA	221 mg/m³
	50 ppm
OEL STEL	442 mg/m³
	100 ppm
Italy - Occupational Exposure Limits	
OEL TWA	221 mg/m³
	50 ppm
OEL STEL	442 mg/m³
	100 ppm
Latvia - Occupational Exposure Limits	
OEL TWA	221 mg/m³
	50 ppm
OEL STEL	442 mg/m³
	100 ppm
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	210 mg/m³
	47,5 ppm
TGG-15min (OEL STEL)	442 mg/m³
	100 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	100 mg/m³
NDSCh (OEL STEL)	200 mg/m³
Romania - Occupational Exposure Limits	
OEL TWA	221 mg/m³
	50 ppm
OEL STEL	442 mg/m³
	100 ppm
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	221 mg/m³
	50 ppm
VLA-EC (OEL STEL)	442 mg/m³
	100 ppm
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	221 mg/m³
	50 ppm
KGV (OEL STEL)	442 mg/m³
	100 ppm

xylene (mixture) (1330-20-7)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	220 mg/m³
	50 ppm
WEL STEL (OEL STEL)	441 mg/m³
	100 ppm
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	108 mg/m³
	25 ppm
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	220 mg/m³
	50 ppm
KZGW (OEL STEL)	440 mg/m³
	100 ppm
USA - ACGIH® - Threshold Limit Values	
ACGIH® TLV® TWA	435 mg/m³
	100 ppm
ACGIH® TLV® STEL	655 mg/m³
	150 ppm

Acetone (67-64-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Acetone
IOEL TWA	1210 mg/m³
	500 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	1200 mg/m³
	500 ppm
MAK (OEL STEL)	4800 mg/m³
	2000 ppm
Belgium - Occupational Exposure Limits	
Local name	Acétone # Aceton
OEL TWA	1210 mg/m³
	500 ppm
OEL STEL	2420 mg/m³
	1000 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 21/01/2020
Denmark - Occupational Exposure Limits	
8-timers grænseværdi (OEL TWA)	600 mg/m³
	250 ppm

Acetone (67-64-1)	
Korttidsgrænseværdi (OEL STEL)	1200 mg/m³
	500 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	1200 mg/m³
	500 ppm
HTP (OEL STEL)	1500 mg/m³
	630 ppm
France - Occupational Exposure Limits	
Local name	Acétone
VLEP 8h (OEL TWA)	1210 mg/m³
	500 ppm
VLEP CT (OEL STEL)	2420 mg/m³
	1000 ppm
Remark	Valeurs règlementaires contraignantes
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487)
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	1200 mg/m³
	500 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	1210 mg/m³
CK (OEL STEL)	2420 mg/m³
Ireland - Occupational Exposure Limits	
OEL TWA	1210 mg/m³
	500 ppm
Italy - Occupational Exposure Limits	
OEL TWA	1210 mg/m³
	500 ppm
Latvia - Occupational Exposure Limits	
OEL TWA	1210 mg/m³
	500 ppm
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	1210 mg/m³
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	600 mg/m³
NDSP (OEL C)	1800 mg/m³
Romania - Occupational Exposure Limits	
OEL TWA	1210 mg/m³
	500 ppm

Acetone (67-64-1)	
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	1210 mg/m³
	500 ppm
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	600 mg/m³
	250 ppm
KGV (OEL STEL)	1200 mg/m³
	500 ppm
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	1210 mg/m³
	500 ppm
WEL STEL (OEL STEL)	3620 mg/m³
	1500 ppm
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	1200 mg/m³
	500 ppm
KZGW (OEL STEL)	2400 mg/m³
	1000 ppm

butane (106-97-8)	
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	1600 mg/m³
	800 ppm
MAK (OEL STEL)	3800 mg/m³
	1600 ppm
Belgium - Occupational Exposure Limits	
Local name	Butane, tous isomères: n-butane # Butaan, alle isomeren: n-butaan
OEL STEL	2370 mg/m³
	980 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
Denmark - Occupational Exposure Limits	
8-timers grænseværdi (OEL TWA)	1200 mg/m³
	500 ppm
Korttidsgrænseværdi (OEL STEL)	2400 mg/m³
	1000 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	1900 mg/m³
	800 ppm
HTP (OEL STEL)	2400 mg/m³
	1000 ppm

butane (106-97-8)	
France - Occupational Exposure Limits	
Local name	n-Butane
VLEP 8h (OEL TWA)	1900 mg/m³
	800 ppm
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	2400 mg/m³
	1000 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	2350 mg/m³
CK (OEL STEL)	9400 mg/m³
Ireland - Occupational Exposure Limits	
OEL STEL	1000 ppm
Latvia - Occupational Exposure Limits	
OEL TWA	300 mg/m³
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	1900 mg/m³
NDSCh (OEL STEL)	3000 mg/m³
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	1935 mg/m³
	800 ppm
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	1450 mg/m³
	600 ppm
WEL STEL (OEL STEL)	1810 mg/m³
	750 ppm
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	1900 mg/m³
	800 ppm
KZGW (OEL STEL)	7600 mg/m³
	3200 ppm
USA - ACGIH® - Threshold Limit Values	
ACGIH® TLV® TWA	1900 mg/m³
	800 ppm

acetone; propan-2-one; propanone (67-64-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	1210 mg/m³
	500 ppm

acetone; propan-2-one; propanone (67-64-1)	
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	1200 mg/m³
	500 ppm
MAK (OEL STEL)	4800 mg/m³
	2000 ppm
Belgium - Occupational Exposure Limits	
OEL TWA	1210 mg/m³
	500 ppm
OEL STEL	2420 mg/m³
	1000 ppm
Denmark - Occupational Exposure Limits	
8-timers grænseværdi (OEL TWA)	600 mg/m³
	250 ppm
Korttidsgrænseværdi (OEL STEL)	1200 mg/m³
	500 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	1200 mg/m³
	500 ppm
HTP (OEL STEL)	1500 mg/m³
	630 ppm
France - Occupational Exposure Limits	
VLEP 8h (OEL TWA)	1210 mg/m³
	500 ppm
VLEP CT (OEL STEL)	2420 mg/m³
	1000 ppm
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	1200 mg/m³
	500 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	1210 mg/m³
CK (OEL STEL)	2420 mg/m³
Ireland - Occupational Exposure Limits	
OEL TWA	1210 mg/m³
	500 ppm
Italy - Occupational Exposure Limits	
OEL TWA	1210 mg/m³
	500 ppm
Latvia - Occupational Exposure Limits	
OEL TWA	1210 mg/m³

acetone; propan-2-one; propanone (67-64-1)	
	500 ppm
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	1210 mg/m³
TGG-15min (OEL STEL)	2420 mg/m³
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	600 mg/m³
NDSP (OEL C)	1800 mg/m³
Romania - Occupational Exposure Limits	
OEL TWA	1210 mg/m³
	500 ppm
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	1210 mg/m³
	500 ppm
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	600 mg/m³
	250 ppm
KGV (OEL STEL)	1200 mg/m³
	500 ppm
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	1210 mg/m³
	500 ppm
WEL STEL (OEL STEL)	3620 mg/m³
	1500 ppm
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	295 mg/m³
	125 ppm
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	1200 mg/m³
	500 ppm
KZGW (OEL STEL)	2400 mg/m³
	1000 ppm

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:
Safety glasses. ISO 16321-1

Eye protection			
Type	**Field of application**	**Characteristics**	**Standard**
Safety glasses		With side shields	EN 166

8.2.2.2. Skin protection

Skin and body protection:
Wear suitable protective clothing

Hand protection:
Gloves. ISO 374-1

Hand protection					
Type	**Material**	**Permeation**	**Thickness (mm)**	**Penetration**	**Standard**
Disposable gloves, Reusable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)		3 (> 0.65)	EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection:
Good ventilation of the workplace required. Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment

Respiratory protection			
Device	**Filter type**	**Condition**	**Standard**
Full face mask		If conc. in air > exposure limit	

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Colour	:	Colourless.
Odour	:	No data available
Odour threshold	:	No data available
pH	:	No data available
Relative evaporation rate (butylacetate=1)	:	No data available

Melting point	:	No data available
Freezing point	:	No data available
Boiling point	:	No data available
Flash point	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Flammability (solid, gas)	:	Extremely flammable aerosol.
Vapour pressure	:	No data available
Relative vapour density at 20°C	:	No data available
Relative density	:	0,84
Solubility	:	No data available
Partition coefficient n-octanol/water (Log Pow)	:	No data available
Viscosity, kinematic	:	20,5 mm²/s
Viscosity, dynamic	:	No data available
Explosive properties	:	No data available
Oxidising properties	:	No data available
Explosive limits	:	No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions. Contains gas under pressure; may explode if heated.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Heat. Open flame. Sparks. Water, humidity. Freezing.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral)	:	Not classified
Acute toxicity (dermal)	:	Not classified
Acute toxicity (inhalation)	:	Not classified

Ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 Inhalation - Rat (Vapours)	17,2 mg/l/4h

xylene (mixture) (1330-20-7)	
LD50 oral rat	4300

xylene (mixture) (1330-20-7)	
LD50 dermal rabbit	1100 mg/kg

Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg (OECD 401)
LD50 dermal rat	> 15800 mg/kg
LC50 Inhalation - Rat	76 mg/l/4h

1,1'-[methylenebis(oxy)]dibutane (2568-90-3)	
LD50 oral rat	6873 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 2184 - 19981
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

butane (106-97-8)	
LC50 Inhalation - Rat	658 mg/l/4h
LC50 Inhalation - Rat (Vapours)	658 mg/l/4h

acetone; propan-2-one; propanone (67-64-1)	
LD50 oral rat	5800 mg/kg (OECD 401)
LD50 dermal rat	> 15800 mg/kg
LC50 Inhalation - Rat	76 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

1,1'-[methylenebis(oxy)]dibutane (2568-90-3)	
NOAEL (animal/male, F0/P)	1000 mg/kg
NOAEL (animal/female, F0/P)	1000 mg/kg
NOAEL (animal/male, F1)	300 mg/kg
NOAEL (animal/female, F1)	300 mg/kg

STOT-single exposure : May cause drowsiness or dizziness. May cause respiratory irritation.

xylene (mixture) (1330-20-7)	
STOT-single exposure	May cause respiratory irritation.

Acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.

acetone; propan-2-one; propanone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Ethylbenzene (100-41-4)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

xylene (mixture) (1330-20-7)	
NOAEC (inhalation, rat, vapour, 90 days)	4,35 mg/l

xylene (mixture) (1330-20-7)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

1,1'-[methylenebis(oxy)]dibutane (2568-90-3)	
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight/day
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	6,3 mg/l

Aspiration hazard : May be fatal if swallowed and enters airways.

CARBURATOR CLEANER BARDAHL	
Vaporizer	Aerosol
Viscosity, kinematic	20,5 mm²/s

1,1'-[methylenebis(oxy)]dibutane (2568-90-3)	
Viscosity, kinematic	1,083 mm²/s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm²/s)'

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short–term (acute) : Not classified

Hazardous to the aquatic environment, long–term (chronic) : Harmful to aquatic life with long lasting effects.

Ethylbenzene (100-41-4)	
LC50 - Fish [1]	4,2 mg/l Oncorhynchus mykiss (truite arc-en-ciel)
EC50 - Crustacea [1]	1,8 – 2,4 mg/l daphnia magna
EC50 72h - Algae [1]	5,4 mg/l Pseudokirchneriella subcapitata
NOEC chronic crustacea	0,96 mg/l (Ceriodaphnia dubia)

xylene (mixture) (1330-20-7)	
LC50 - Fish [1]	2,6 mg/l Oncorhynchus mykiss (Rainbow trout)
EC50 - Crustacea [1]	1 – 5 mg/l Daphnia magna (Water flea)
EC50 72h - Algae [1]	3 – 5 mg/l algae
ErC50 algae	4,36 mg/l Pseudokirchneriella subcapitata

Acetone (67-64-1)	
LC50 - Fish [1]	5540 mg/l (Oncorhynchus mykiss)
LC50 - Fish [2]	11000 mg/l (Alburnus alburnum)
LC50 - Other aquatic organisms [1]	> 100 mg/l
EC50 - Crustacea [1]	8800 mg/l (Daphnia pulex)
EC50 - Other aquatic organisms [1]	2100 mg/l (24h, Artemisia salina)
NOEC (acute)	430 mg/l (96h, Prorocentrum minimum)
NOEC (chronic)	530 mg/l (8h, algues, Microcystis aeruginosa)

1,1'-[methylenebis(oxy)]dibutane (2568-90-3)	
LC50 - Fish [1]	27,344 mg/l Test organisms (species): other:
EC50 - Crustacea [1]	> 28,7 mg/l Test organisms (species): Daphnia magna

1,1'-[methylenebis(oxy)]dibutane (2568-90-3)	
EC50 72h - Algae [1]	> 1,3 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
NOEC chronic fish	2,903 mg/l Fathead minnow (Pimephales promelas) - 28 days
NOEC chronic crustacea	1,7 mg/l Daphnia magma 21 days

butane (106-97-8)	
LC50 - Fish [1]	680 mg/l

acetone; propan-2-one; propanone (67-64-1)	
LC50 - Fish [1]	5540 mg/l (Oncorhynchus mykiss)
LC50 - Fish [2]	11000 mg/l (Alburnus alburnum)
EC50 - Crustacea [1]	8800 mg/l (Daphnia pulex)
EC50 - Other aquatic organisms [1]	2100 mg/l (24h, Artemisia salina)
NOEC (acute)	430 mg/l (96h, Prorocentrum minimum)
NOEC (chronic)	530 mg/l (8h, algues, Microcystis aeruginosa)
NOEC chronic fish	430 mg/l (Prorocentrum minimum)
NOEC chronic algae	530 mg/l (Microcystis aeruginosa)

12.2. Persistence and degradability

Ethylbenzene (100-41-4)	
Persistence and degradability	Readily biodegradable.
Biodegradation	70 – 80 % (28 jours - OECD 301E) 100% (6 jours - OECD 301E)

xylene (mixture) (1330-20-7)	
Persistence and degradability	Readily biodegradable.
Biodegradation	87,8 % 28 days

Acetone (67-64-1)	
Persistence and degradability	Readily biodegradable.
ThOD	2,21 g O_2/g substance
BOD (% of ThOD)	84 % ThOD (BOD5, APHA 219)
Biodegradation	91 % (28 days, OCDE 301B)

butane (106-97-8)	
Persistence and degradability	Readily biodegradable.

acetone; propan-2-one; propanone (67-64-1)	
Persistence and degradability	Readily biodegradable.
ThOD	2,21 g O_2/g substance
BOD (% of ThOD)	84 % ThOD (BOD5, APHA 219)
Biodegradation	91 % (28 days, OCDE 301B)

12.3. Bioaccumulative potential

Ethylbenzene (100-41-4)	
BCF - Fish [1]	< 100

Ethylbenzene (100-41-4)	
Partition coefficient n-octanol/water (Log Pow)	3,5

xylene (mixture) (1330-20-7)	
BCF - Fish [1]	5,4 – 25,9 Oncorhynchus mykiss (Rainbow trout)
Partition coefficient n-octanol/water (Log Pow)	2,77 – 3,2
Bioaccumulative potential	not bioaccumulable.

Acetone (67-64-1)	
Partition coefficient n-octanol/water (Log Pow)	-0,24

1,1'-[methylenebis(oxy)]dibutane (2568-90-3)	
Bioconcentration factor (BCF REACH)	30,38
Partition coefficient n-octanol/water (Log Pow)	2,77

butane (106-97-8)	
Bioaccumulative potential	not bioaccumulable.

acetone; propan-2-one; propanone (67-64-1)	
Bioconcentration factor (BCF REACH)	3 (BCFWIN v2.17)
Partition coefficient n-octanol/water (Log Pow)	-0,24

12.4. Mobility in soil

Ethylbenzene (100-41-4)	
Ecology - soil	insoluble in water.

1,1'-[methylenebis(oxy)]dibutane (2568-90-3)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2,265

12.5. Results of PBT and vPvB assessment

Component	
xylene (mixture) (1330-20-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Sewage disposal recommendations : Do not discharge into drains or the environment.

Product/Packaging disposal recommendations : Collect all waste in suitable and labelled containers and dispose according to local legislation. Dispose used or damaged aerosol cans at permitted disposal sites.

Additional information : Empty the packaging completely prior to disposal. Do not re-use empty containers.

Ecological waste information : Do not discharge the product into the environment.

European List of Waste (LoW, EC 2000/532) : 16 05 04* - gases in pressure containers (including halons) containing dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID

ADR	IMDG	IATA	RID
14.1. UN number			
UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name			
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS
Transport document description			
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1
14.3. Transport hazard class(es)			
2.1	2.1	2.1	2.1
			
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available			

14.6. Special precautions for user

Overland transport

Classification code (ADR) : 5F
Special provisions (ADR) : 190, 327, 344, 625
Limited quantities (ADR) : 1l
Excepted quantities (ADR) : E0
Packing instructions (ADR) : P207
Special packing provisions (ADR) : PP87, RR6, L2
Mixed packing provisions (ADR) : MP9
Transport category (ADR) : 2
Special provisions for carriage - Packages (ADR) : V14
Special provisions for carriage - Loading, unloading and handling (ADR) : CV9, CV12
Special provisions for carriage - Operation (ADR) : S2
Tunnel restriction code (ADR) : D

Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG) : P207, LP200
Special packing provisions (IMDG) : PP87, L2
EmS-No. (Fire) : F-D
EmS-No. (Spillage) : S-U
Stowage category (IMDG) : None
Stowage and handling (IMDG) : SW1, SW22
Segregation (IMDG) : SG69

Air transport

PCA Excepted quantities (IATA)	:	E0
PCA Limited quantities (IATA)	:	Y203
PCA limited quantity max net quantity (IATA)	:	30kgG
PCA packing instructions (IATA)	:	203
PCA max net quantity (IATA)	:	75kg
CAO packing instructions (IATA)	:	203
CAO max net quantity (IATA)	:	150kg
Special provisions (IATA)	:	A145, A167, A802
ERG code (IATA)	:	10L

Rail transport

Classification code (RID)	:	5F
Special provisions (RID)	:	190, 327, 344, 625
Limited quantities (RID)	:	1L
Excepted quantities (RID)	:	E0
Packing instructions (RID)	:	P207, LP200
Special packing provisions (RID)	:	PP87, RR6, L2
Mixed packing provisions (RID)	:	MP9
Transport category (RID)	:	2
Special provisions for carriage – Packages (RID)	:	W14
Special provisions for carriage - Loading, unloading and handling (RID)	:	CW9, CW12
Colis express (express parcels) (RID)	:	CE2
Hazard identification number (RID)	:	23

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)	
Reference code	**Applicable on**
3(a)	CARBURATOR CLEANER BARDAHL ; xylene (mixture) ; Acetone ; acetone; propan-2-one; propanone
3(b)	CARBURATOR CLEANER BARDAHL ; xylene (mixture) ; Acetone ; acetone; propan-2-one; propanone
3(c)	CARBURATOR CLEANER BARDAHL ; xylene (mixture)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Not listed on the Ozone Depletion list (Regulation EU 2024/590)
Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Detergent Regulation (EC 648/2004)

Labelling of contents	
Component	**%**
aliphatic hydrocarbons	≥30%
aromatic hydrocarbons	15-30%

Seveso Directive (Disaster Risk Reduction)

Seveso III Part I (Categories of dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
P3a FLAMMABLE AEROSOLS 'Flammable' aerosols Category 1 or 2, containing flammable gases Category 1 or 2 or flammable liquids Category 1	150	500

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG). Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).

Override matching entry (12. BImSchV) : Is not subject to the Major Accidents Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed

SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed

SZW-lijst van reprotoxische stoffen – Ontwikkeling : xylene (mixture) is listed

Denmark

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with it.
If an employee is pregnant or breastfeeding and the person in question uses or is exposed to this product at work, the employer must always carry out a risk assessment of the work. The assessment must both deal with the dangerousness of the impact and its strength and duration. The employer's decision that a pregnant or lactating woman can perform a specific work task must therefore be made in the context of her specific working conditions. See also WEA-Guideline A.1.8-7 on the working environment of pregnant and breastfeeding workers.
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

Switzerland

Storage class (LK) : LK 2 - Liquefied or pressurized gases

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.

Full text of H- and EUH-statements:	
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.