XTRM 15W40

SUPERCHARGED C60 FULLERENE

DESCRIPTION

Mineral engine oil for passenger cars and delivery vans. Ideal for multi-fleet applications. Compatible with petrol, diesel and LPG cars, turbo-charged or not and equipped or not with a catalytic converter. This new oil contains the **famous additives BARDAHL C60 and POLAR PLUS (Extreme Pressure, anti-wear and anti-friction properties). It extends the oil intervals. Bardahl XTRM 15w40 will improve the engine oil temperature and avoids premature engine wear, extends the engine lifespan with optimal performances.**

APPLICATION

BARDAHL XTRM 15w40 C60 can be used all year long in hard - even very hard - conditions and dusty environment. It offers excellent cleaning properties and a very good protection against wear. **Its thermal stability offers a longer protection of any kind of surfaces.**

SPECIFICATIONS

This product offers the following performance level:

ACEA	E7
API	CI-4/SJ
MB	228.3
MAN	3275-1
CAT	ECF-1-a
CUMMINS	CES 20076/20077
MTU	Type 2
DEUTZ	DQC III-18
VOLVO	VDS3
RENAULT	RLD-2
JASO	DH-1

PROPERTIES

- ✓ Avoids deposits on pistons,
- ✓ Provides excellent cleaning properties,
- ✓ Anti-wear,
- ✓ Anti-friction,
- ✓ Extreme pressure.

SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers,3, ZI Tournai Ouest II
T: (+32) (0) 69 59 03 60
www.bardahl.be
www.bardahloils.com

TECHNICAL DATA

Density at 20°C	Kg/l	0,868
Viscosity at -20°C	cP	3960
Viscosity at 40°C	mm2/s	95,20
Viscosity at 100°C	mm2/s	14,10
Viscosity index		152
Flash point COC, °C	°C	220
Pour point, °C	°C	-33
TBN	mgKOH/g	11,1
Sulphated ash contents	%	1,2

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 36 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36943	3 x 5 L
36947	205 L

SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers,3, ZI Tournai Ouest II
T: (+32) (0) 69 59 03 60
www.bardahl.be
www.bardahloils.com