ATF +4

DESCRIPTION

Synthetic automatic fluid formulated with « friction modifiers » and recommended for the automatic transmissions of Chrysler, Jeep and many other vehicles (see Specifications) requiring special friction properties. This fluid can be used in **steering wheels and hydraulic systems.**

APPLICATION

BARDAHL ATF+4 provides an excellent stability and fluidity at low temperature. Ideal for cold starting.

SPECIFICATIONS

This product offers the following performance level:

- Aisin Warner JWS 3309/3324 / AW-1
- Allison C3/C4/TES-228
- BMW ATF 6 / 7045E/8072B/LA2634/LT71141
- CAT-TO-2, Chrysler ATF+/+2/ATF+3/ATF+4
- Ford Mercon/M2C 138CJ/166H/922-A1/924-A
- GM Dexron IID/IIE/IIIG/IIIH, TASA
- Honda DW-1 / ATF-Z1 (except in CVT)
- Hyundai/Kia SP-II/SP-III/ SP-IV / JWS 3314/9638
- Isuzu Besco ATF II/III
- JASO M 315-2013 Type 1A
- Mazda ATF M-V / M-III, DTFR 13C100 / 13C140 / 13C150 / 13C170
- MB 236.1/236.6/236.7/236.8/236.9/236.10 / 236.93
- Nissan Matic Fluid C/D/J/K / S
- Subaru ATF/ATF 5AT/ATF HP/Dexron II
- Suzuki ATF 3314/3317
- Toyota ATF T-III/T-IV/D-II/D-III/WS
- Volvo 1161540
- VW G 055 025 / 052 162 / 055 005 / 060 162
- ZF TE-ML 09/11A/11B, Shell ATF 3403-M115

SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers,3, ZI Tournai Ouest II
T: (+32) (0) 69 59 03 60
www.bardahl.be
www.bardahloils.com

PROPERTIES

- ✓ Has a high viscosity index ensuring a very good stability,
- ✓ Has a very low pour point,
- ✓ Offers a very good protection against oxidation,
- ✓ Provides anti wear, anticorrosion and antifoam properties,
- ✓ Contains antifriction additives for a smooth and silent change of gear,
- ✓ Does not damage synthetic gaskets,
- ✓ Circulates quickly at cold start,
- ✓ Red color.

TECHNICAL DATA

Density at 15°C	Kg/l	0,848
Viscosity 40°C	mm2/s	36,6
Viscosity 100°C	mm2/s	7,2
Viscosity Index		165
Flash point COC, °C	°C	212
Pour point, °C	°C	-48
TBN alcalinity	mgKOH/g	2,7

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36551	12 x 1 L
36558	20 L

SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers,3, ZI Tournai Ouest II
T: (+32) (0) 69 59 03 60
www.bardahl.be
www.bardahloils.com