TECHNICAL DATA SHEET
V032026

XTG 80W90

DESCRIPTION

Mineral extreme pressure gear oil formulated for the lubrication of heavy loaded mechanical transmissions: gearboxes, transaxles and differentials.

APPLICATION

BARDAHL XTG 80w90 is particularly suitable for heavy loaded hypoid differentials.

SPECIFICATIONS

This product offers the following performance level:

API	GL5
MIL	L-2105D
MAN	342 Typ M2
ZF	TE-ML 05A/7A/12E/16B/16C/17B/19B/21A

PROPERTIES

- ✓ Offers very strong extreme pressure (EP) properties,
- ✓ Has a low pour point,
- ✓ Provides a high resistance against corrosion and oxidation,
- ✓ Provides anti-wear and antifoam properties.

TECHNICAL DATA

Density at 15°C	Kg/l	0,879
Viscosity at 40°C	mm2/s	150,5
Viscosity at 100°C	mm2/s	15,8
Viscosity index		102
Flash point COC, °C	°C	214
Pour point, °C	°C	-27

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet. Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36271	12 x 1 L
36273	3 x 5 L
36278	20 L
36274	60 L
36277	205 L

SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers,3, ZI Tournai Ouest II
T: (+32) (0) 69 59 03 60
www.bardahl.be
www.bardahloils.com