XTEC 0W30

DESCRIPTION

High performance 100% synthetic oil with low ash content developed to extend the lifespan and protect the efficiency of emission reduction systems on diesel and petrol vehicles.

APPLICATION

BARDAHL XTEC 0w30 has been developed according to the Mid S.A.P.S./low HTHS technology and can be used in any engine requiring a diesel or petrol engine oil with the Peugeot Citroën B71 2312 oil performance level.

SPECIFICATIONS

This product offers the following performance level:

ACEA	C2
API	SP
FIAT	9.55535-GS1/DS1
PSA	B71-2312 / B71-2302
STELLANTIS	FPW 9.55535-02

PROPERTIES

- ✓ Avoids fuel overconsumption.
- ✓ Preserves the lubricating film at high temperature,
- ✓ Offers excellent dispersion and detergency properties,
- ✓ Makes cold starting easier,
- ✓ Offers a high protection against oxidation.

SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers,3, ZI Tournai Ouest II
T: (+32) (0) 69 59 03 60
www.bardahl.be
www.bardahloils.com

TECHNICAL DATA

Density at 15°C	Kg/l	0,848
Viscosity at -35°C	mPa.s	5540
Viscosity at 40°C	mm2/s	53,6
Viscosity at 100°C	mm2/s	9,7
Viscosity index		168
Flash point COC, °C	°C	230
Pour point, °C	°C	-48
TBN alcalinity	mgKOH/g	6,2
Sulphated ash contents	%	0,59

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling: any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36521	12 x 1 L
36522	4 x 4L
36523	3 x 5 L
36528	1 x 20L
36524	1 x 60L
36527	1 x 205 L

SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers,3, ZI Tournai Ouest II
T: (+32) (0) 69 59 03 60
www.bardahl.be
www.bardahloils.com