TECHNICAL DATA SHEET
V112026

# XTG DCT MULTI

## DESCRIPTION

Very high performance fluid formulated for DCT (Dual Clutch Transmission) gearboxes and transmissions: DSG, DCT, DKG, PDK, DCS, EDC, DC4, GR6, Powershift, S-tronic, etc.

## APPLICATION

**BARDAHL XTG DCT** is particularly suitable for « WET » or « DRY » DCT transmissions. It enables to avoid fuel over-consumption.

## SPECIFICATIONS

This product offers the following performance level:

| | |
|---|---|
| BMW | DCTF-1 / 1+ / 2 / LT-5 |
| BORG WARNER | |
| DTFR | 13C130 |
| BUGATTI VEYRON | |
| CHRYSLER | 68044345 EA & GA |
| FERRARI | TF DCT-F3 |
| FIAT | 9.55550-HE2 / MZ6 |
| FORD | WSS-M2C936-A / WSS-M2C218-A1 / M2C200-D2 |
| HYUNDAI/KIA | |
| MERCEDES-BENZ | 236.21 / 236.22 / 236.23 / 236.24 / 236.25 / 239.21 |
| MITSUBISHI | DIA-QUEEN SSTF-1 |
| PORSCHE | ZF FFL-3 |
| PSA | 9734 S2 |
| RENAULT | EDC / DC4 / DW5 / DW6 |
| VOLVO | 1161383/1161839/D1/D2 |
| VW | G-052-529 / G-052-182 / G-055-529 A1 A2 / G 052 536 / G 055 536 / 052 549 / 052 524 |

## PROPERTIES

- ✓ Has a very high and stable viscosity index,
- ✓ Has a very low pour point,
- ✓ Is compatible with synthetic seals,
- ✓ Offers ideal friction performance,
- ✓ Provides anti-vibration performance,
- ✓ Extends the oil drain interval,
- ✓ Provides a good resistance against oxidation and corrosion,
- ✓ Offers anti-wear, anti-foam and anti-shudder properties.


SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers,3, ZI Tournai Ouest II
T: (+32) (0) 69 59 03 60
www.bardahl.be
www.bardahloils.com

## TECHNICAL DATA

| | | |
|---|---|---|
| **Density at 15°C** | Kg/l | 0,85 |
| **Viscosity at 40°C** | mm2/s | 34 |
| **Viscosity at 100°C** | mm2/s | 7,17 |
| **Viscosity Index** | | 183 |
| **Flash point COC, °C** | °C | 201 |
| **Pour point, °C** | °C | -48 |

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

## RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

## REFERENCES & AVAILABILITIES

| | |
|---|---|
| 36511 | 12 x 1 L |
| 36518 | 20 L |
| 36517 | 205 L |


SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers,3, ZI Tournai Ouest II
T: (+32) (0) 69 59 03 60
www.bardahl.be
www.bardahloils.com