FUEL STABILIZER MOTO

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Reference number: 2804
Issue date: 22-04-26 Revision date: 22-04-26 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : FUEL STABILIZER MOTO
UFI : TWNG-92MK-Q80G-XK0C
Product code : 2804 # 734280R0

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Consumer use
Function or use category : Fuel additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Distributor
SADAPS BARDAHL Additives & Lubricants
ZI TOURNAI OUEST 2 - RUE DU MONT DES CARLIERS, 3
7522 TOURNAI
BELGIQUE
T +32 (0).69.59.03.60, F +32 (0).69.59.03.61
msds@bardahlfrance.com, www.bardahl.be

Supplier
SADAPS BARDAHL Additives & Lubricants
ZI TOURNAI OUEST 2 - RUE DU MONT DES CARLIERS, 3
7522 TOURNAI
BELGIQUE
T +32 (0).69.59.03.60, F +32 (0).69.59.03.61
msds@bardahlfrance.com, www.bardahl.be

1.4. Emergency telephone number

Emergency number : + 32 (0)70.245.245 / +33 (0)1.45.42.59.59

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals-24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital Msida MSD 2090 Msida	112 +356 2545 6508	
Saudi Arabia	Poison Control Center-Riyadh	General Directorate of Health Affairs Medial Province	+966 112324180 +966 112324189	
United Arab Emirates	Health Authority – Abu Dhabi (HAAD) Poison & Drug Information Center (PDIC)	P.O. Box 5674	+ 800-424	
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER	+44 20 7188 7188	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2	H315
Aspiration hazard, Category 1	H304
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07 GHS08

Signal word (CLP) : Danger

Contains : Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hazard statements (CLP) : H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P264 - Wash hands thoroughly after handling.
P273 - Avoid release to the environment.
P280 - Wear protective gloves.
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER, a doctor.
P331 - Do NOT induce vomiting.
P405 - Store locked up.
P501 - Dispose of contents/container to a hazardous or special waste collection point.

Child-resistant fastening : Applicable

Tactile warning : Applicable

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

Component	
2,6-di-tert-butylphenol (128-39-2)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics substance with national workplace exposure limit(s) (FR)	EC-No.: 918-481-9 REACH-no: 01-2119457273-39	70 - 90	Asp. Tox. 1, H304 EUH066
2-ethylhexan-1-ol substance with national workplace exposure limit(s) (AT, BE, DE, DK, ES, FI, FR, GB, HU, IE, IT, LV, NL, PL, RO, SE); substance with a Community workplace exposure limit	CAS-No.: 104-76-7 EC-No.: 203-234-3 REACH-no: 01-2119487289-20	5 - 10	Acute Tox. 4 (Inhalation), H332 (ATE=11 mg/l) Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Chronic 3, H412
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	EC-No.: 918-481-9 REACH-no: 01-2119457273-39	5 - 10	Asp. Tox. 1, H304 EUH066
2,6-di-tert-butylphenol	CAS-No.: 128-39-2 EC-No.: 204-884-0 REACH-no: 01-2119490822-33	<3	Skin Irrit. 2, H315 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)
diphenylamine	CAS-No.: 122-39-4 EC-No.: 204-539-4 EC Index-No.: 612-026-00-5 REACH-no: 01-2119488966-13	<0,1	Acute Tox. 3 (Oral), H301 (ATE=100 mg/kg bodyweight) Acute Tox. 3 (Dermal), H311 (ATE=300 mg/kg bodyweight) Acute Tox. 3 (Inhalation), H331 (ATE=0,5 mg/l/4h) Eye Irrit. 2, H319 Carc. 2, H351 STOT RE 2, H373 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If medical advice is needed, have product container or label at hand.

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

First-aid measures after skin contact : Remove contaminated clothes. Wash skin with plenty of water. Wash contaminated clothing before reuse.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

First-aid measures after ingestion : Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May be fatal if swallowed and enters airways.

Symptoms/effects after inhalation : May be fatal if swallowed and enters airways.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after ingestion : May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Water spray. Dry powder. Foam.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.
Other information : Prevent liquid from entering sewers, watercourses, underground or low areas.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area. Eliminate every possible source of ignition. Ensure adequate ventilation, especially in confined areas. Keep public away from danger area. Equip cleanup crew with proper protection.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Dike for recovery or absorb with appropriate material. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Recover the product with absorbent material.
Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not eat, drink or smoke when using this product.
Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Provide local exhaust or general room ventilation.
Storage conditions : Store in a closed container. Keep out of frost.
Heat and ignition sources : Keep away from naked flames/heat. Keep away from ignition sources.
Storage area : Store in a dry place. Store in a well-ventilated place.
Special rules on packaging : Store in original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
France - Occupational Exposure Limits	
VLEP 8h (OEL TWA)	1200 mg/m³
	184 ppm

2-ethylhexan-1-ol (104-76-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	2-ethylhexan-1-ol
IOEL TWA	5,4 mg/m³
	1 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	5,4 mg/m³
	1 ppm
MAK (OEL STEL)	10,8 mg/m³
	2 ppm
Belgium - Occupational Exposure Limits	
Local name	2-Ethylhexan-1-ol # Ethylhexaan-1-ol
OEL TWA	5,4 mg/m³
	1 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
Denmark - Occupational Exposure Limits	
8-timers grænseværdi (OEL TWA)	5,4 mg/m³
	1 ppm
Korttidsgrænseværdi (OEL STEL)	10,8 mg/m³
	2 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	5,4 mg/m³
	1 ppm
France - Occupational Exposure Limits	
Local name	2-Ethylhexan-1-ol
VLEP 8h (OEL TWA)	5,4 mg/m³
	1 ppm
Remark	Valeurs réglementaires indicatives
Regulatory reference	Arrêté du 30 juin 2004 modifié (réf.: INRS ED 6443, 2022; Outil65; Arrête du 27 septembre 2019)
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	54 mg/m³

2-ethylhexan-1-ol (104-76-7)	
	10 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	5,4 mg/m³
Ireland - Occupational Exposure Limits	
OEL TWA	5,4 mg/m³
	1 ppm
Italy - Occupational Exposure Limits	
OEL TWA	5,4 mg/m³
	1 ppm
Latvia - Occupational Exposure Limits	
OEL TWA	5,4 mg/m³
	1 ppm
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	5,4 mg/m³
	1 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	5,4 mg/m³
	1 ppm
NDSCh (OEL STEL)	10,8 mg/m³
	2 ppm
Romania - Occupational Exposure Limits	
OEL TWA	5,4 mg/m³
	1 ppm
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	5,4 mg/m³
	1 ppm
VLA-EC (OEL STEL)	110 mg/m³
	20 ppm
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	5,4 mg/m³
	1 ppm
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	5,4 mg/m³
	1 ppm
WEL STEL (OEL STEL)*	16,2 mg/m³
	3 ppm
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	5,4 mg/m³
	1 ppm

2-ethylhexan-1-ol (104-76-7)	
Korttidsverdi (OEL STEL)	54 mg/m³
	10 ppm
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	5,4 mg/m³
	1 ppm
KZGW (OEL STEL)	10,8 mg/m³
	2 ppm

2-ethylhexan-1-ol (104-76-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	2-ethylhexan-1-ol
IOEL TWA	5,4 mg/m³
	1 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	5,4 mg/m³
	1 ppm
MAK (OEL STEL)	10,8 mg/m³
	2 ppm
Belgium - Occupational Exposure Limits	
OEL TWA	5,4 mg/m³
	1 ppm
Denmark - Occupational Exposure Limits	
8-timers grænseværdi (OEL TWA)	5,4 mg/m³
	1
Korttidsgrænseværdi (OEL STEL)	10,8 mg/m³
	2 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	5,4 mg/m³
	1 ppm
France - Occupational Exposure Limits	
VLEP 8h (OEL TWA)	5,4 mg/m³
	1 ppm
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	54 mg/m³
	10 ppm
Ireland - Occupational Exposure Limits	
OEL TWA	5,4 mg/m³
	1 ppm

2-ethylhexan-1-ol (104-76-7)	
Latvia - Occupational Exposure Limits	
OEL TWA	5,4 mg/m³
	1 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	5,4 mg/m³
NDSP (OEL C)	10,8 mg/m³
Romania - Occupational Exposure Limits	
OEL TWA	5,4 mg/m³
	1 ppm
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	5,4 mg/m³
	1 ppm
VLA-EC (OEL STEL)	110 mg/m³
	20 ppm
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	5,4 mg/m³
	1 ppm
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	5,4 mg/m³
WEL STEL (OEL STEL)*	16,2 mg/m³
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	5,4 mg/m³
	1 ppm
KZGW (OEL STEL)	10,8 mg/m³
	2 ppm

diphenylamine (122-39-4)	
France - Occupational Exposure Limits	
VLEP 8h (OEL TWA)	10 mg/m³
Ireland - Occupational Exposure Limits	
OEL TWA	10 mg/m³
OEL STEL	20 mg/m³
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	10 mg/m³
WEL STEL (OEL STEL)	20 mg/m³

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:
Safety glasses. ISO 16321-1

8.2.2.2. Skin protection

Skin and body protection:
Wear suitable protective clothing

Hand protection:
Gloves. ISO 374-1. Protective gloves against chemicals (EN 374)

8.2.2.3. Respiratory protection

Respiratory protection:
Good ventilation of the workplace required

Respiratory protection			
Device	**Filter type**	**Condition**	**Standard**
Half-mask		Dust protection	EN 149

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Colour	:	red.
Appearance	:	clear.
Odour	:	Not available
Odour threshold	:	Not available
Melting point	:	Not available
Freezing point	:	Not available
Boiling point	:	Not available
Flammability	:	Not available
Explosive limits	:	Not available
Lower explosion limit	:	Not available
Upper explosion limit	:	Not available
Flash point	:	> 60 °C

Auto-ignition temperature	:	Not available
Decomposition temperature	:	Not available
pH	:	Not available
Viscosity, kinematic	:	< 20,5 mm²/s (40°C)
Solubility	:	Not available
Partition coefficient n-octanol/water (Log Kow)	:	Not available
Vapour pressure	:	Not available
Vapour pressure at 50°C	:	Not available
Density	:	0,794 – 0,809 g/cm³ (20°C)
Relative density	:	Not available
Relative vapour density at 20°C	:	Not available
Particle characteristics	:	Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Heat. Open flame. Sparks. Water, humidity. Freezing.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	:	Not classified
Acute toxicity (dermal)	:	Not classified
Acute toxicity (inhalation)	:	Not classified

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 Inhalation - Rat (Vapours)	> 5 mg/l/4h

2-ethylhexan-1-ol (104-76-7)	
LD50 oral rat	≈ 2047 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)

2-ethylhexan-1-ol (104-76-7)	
LD50 dermal rat	> 3000 mg/kg (OECD 402 method)
LC50 Inhalation - Rat	0,89 – 5,3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

2,6-di-tert-butylphenol (128-39-2)	
LD50 oral rat	1320 mg/kg
LD50 dermal rabbit	10 g/kg

2-ethylhexan-1-ol (104-76-7)	
LD50 oral rat	> 3290 mg/kg
LD50 dermal rabbit	> 3000 mg/kg

diphenylamine (122-39-4)	
LD50 oral rat	100 mg/kg
LD50 dermal rabbit	300 mg/kg

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

2-ethylhexan-1-ol (104-76-7)	
NOAEL (chronic, oral, animal/male, 2 years)	500 mg/kg bodyweight (OECD 451 method)
NOAEL (chronic, oral, animal/female, 2 years)	500 mg/kg bodyweight (OECD 451 method)

Reproductive toxicity : Not classified
STOT-single exposure : Not classified

2-ethylhexan-1-ol (104-76-7)	
STOT-single exposure	May cause respiratory irritation.

2-ethylhexan-1-ol (104-76-7)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : Not classified

2-ethylhexan-1-ol (104-76-7)	
NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, gas, 90 days)	120 ppm Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)

diphenylamine (122-39-4)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : May be fatal if swallowed and enters airways.

FUEL STABILIZER MOTO	
Viscosity, kinematic	< 20,5 mm²/s (40°C)

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Viscosity, kinematic	1,3 mm²/s

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short–term (acute) : Not classified
Hazardous to the aquatic environment, long–term (chronic) : Harmful to aquatic life with long lasting effects.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
LC50 - Fish [1]	> 1000 mg/l
EC50 - Crustacea [1]	> 1000 mg/l Daphnia Magna
EC50 72h - Algae [1]	> 1000 mg/l Pseudokirchnerella subcapitata
NOEC chronic algae	1000 mg/l Pseudokirchnerella subcapitata

2-ethylhexan-1-ol (104-76-7)	
LC50 - Fish [1]	17,1 mg/l Test organisms (species): Leuciscus idus melanotus
LC50 - Fish [2]	28,2 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	39 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	11,5 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	16,6 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

2,6-di-tert-butylphenol (128-39-2)	
LC50 - Fish [1]	1,4 mg/l (Fathead Minnow, 4 d)
LC50 - Fish [2]	13 mg/l (Rainbow Trout, 4 d)
EC50 - Crustacea [1]	0,45 – 0,8 mg/l (Water flea (Daphnia magna), 2 d)
EC50 72h - Algae [1]	3,6 mg/l (Green algae (Selenastrum capricornutum), 3 d)

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
EC50 - Other aquatic organisms [1]	> 1000 mg/l (Water Flea (Daphnia Magna))
EC50 72h - Algae [1]	> 1000 mg/l (Pseudokirchneriella subcapitata)

2-ethylhexan-1-ol (104-76-7)	
LC50 - Fish [1]	28,2 mg/l (Pimephales promelas, 4DY)
EC50 - Crustacea [1]	39 mg/l (Daphnia magma)
EC50 72h - Algae [1]	16,6 mg/l (Scenedesmus quadricaudra)

diphenylamine (122-39-4)	
LC50 - Fish [1]	2,2 mg/l
EC50 - Crustacea [1]	0,31 mg/l (Daphnia magna)
EC50 72h - Algae [1]	1,51 mg/l (Selenastrum capricornutum)

12.2. Persistence and degradability

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Biodegradation	80 % 28 days

2,6-di-tert-butylphenol (128-39-2)	
Persistence and degradability	Not readily biodegradable.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Persistence and degradability	Readily biodegradable.

diphenylamine (122-39-4)	
Biodegradation	26 % (28d) (OCDE 301D method)

12.3. Bioaccumulative potential

2-ethylhexan-1-ol (104-76-7)	
Partition coefficient n-octanol/water (Log Kow)	2,9 (OECD 117 method)

2,6-di-tert-butylphenol (128-39-2)	
Partition coefficient n-octanol/water (Log Pow)	4,5

2-ethylhexan-1-ol (104-76-7)	
Partition coefficient n-octanol/water (Log Pow)	2,9 (measured)

diphenylamine (122-39-4)	
Partition coefficient n-octanol/water (Log Pow)	3,4 (calculé)

12.4. Mobility in soil

2-ethylhexan-1-ol (104-76-7)	
Surface tension	47 mN/m (OECD 115 method)

2-ethylhexan-1-ol (104-76-7)	
Mobility in soil	-1,42

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Sewage disposal recommendations : Do not discharge into drains or the environment.

Product/Packaging disposal recommendations : Collect all waste in suitable and labelled containers and dispose according to local legislation.

Additional information : Empty the packaging completely prior to disposal. Do not re-use empty containers.

Ecological waste information : Do not discharge the product into the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID

ADR	IMDG	IATA	RID
14.1. UN number or ID number			
Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name			
Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)			
Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available			

14.6. Special precautions for user

Overland transport
Not applicable

Transport by sea
Not applicable

Air transport
Not applicable

Rail transport
Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)	
Reference code	**Applicable on**
3(b)	FUEL STABILIZER MOTO ; Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics ; 2-ethylhexan-1-ol ; 2,6-di-tert-butylphenol ; Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics
3(c)	FUEL STABILIZER MOTO ; 2-ethylhexan-1-ol ; 2,6-di-tert-butylphenol

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals): Diphenylamine (122-39-4)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Not listed on the Ozone Depletion list (Regulation EU 2024/590)
Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

Austria

Ordinance on Flammable Liquids (VbF) : Auto detect

France

Occupational diseases	
Code	Description
RG 15	Diseases caused by aromatic amines, their salts and derivatives, especially hydroxylated, halogenated, nitrated, nitrosated and sulphonated
RG 15 BIS	Allergic mechanism disorders caused by aromatic amines, their salts, their derivatives, especially hydroxylated, halogenated, nitrated, nitrosated, sulphonated and products containing them in the free state
RG 49	Skin disorders caused by aliphatic, alicyclic amines or ethanolamines
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG).
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).
Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).
Override matching entry (12. BImSchV) : Is not subject to the Major Accidents Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed
SZW-lijst van mutagene stoffen : None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with it.
If an employee is pregnant or breastfeeding and the person in question uses or is exposed to this product at work, the employer must always carry out a risk assessment of the work. The assessment must both deal with the dangerousness of the impact and its strength and duration. The employer's decision that a pregnant or lactating woman can perform a specific work task must therefore be made in the context of her specific working conditions. See also WEA-Guideline A.1.8-7 on the working environment of pregnant and breastfeeding workers.

Switzerland

Storage class (LK) : LK 6.1 - Toxic materials

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.