# XTS 0W40

## DESCRIPTION

Fully synthetic engine oil formulated with last generation performance additives to reduce friction, eliminate sludge and optimize fuel consumption. Offers a good general protection of the engine.

## APPLICATION

**BARDAHL XTS 0w40** provides an excellent resistance against shearing. It is suitable for powerful engines, turbo-charged or not, with or without direct injection. Compatible with any type of fuel.

## SPECIFICATIONS

This product offers the following performance level:

| | |
|---|---|
| ACEA | A3/B4 |
| API | SP/CF |
| MERCEDES BENZ | 229.3 / 226.5 / 229.5 |
| VW | 502.00/505.00 |
| BMW | Longlife-01 |
| RENAULT | RN0700/RN0710 |
| PORSCHE | A40 |

## PROPERTIES

- ✓ Offers a stable viscosity and a high Viscosity Index,
- ✓ Preserves the protective lubricating film at high temperature,
- ✓ Offers excellent dispersion and detergency properties,
- ✓ Makes cold start easier,
- ✓ Provides an excellent resistance against « shearing ».


SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers,3, ZI Tournai Ouest II
T: (+32) (0) 69 59 03 60
www.bardahl.be
www.bardahloils.com

## TECHNICAL DATA

| | | |
|---|---|---|
| **Density at 15°C** | Kg/l | 0,846 |
| **Viscosity at -35°C** | mPa.s | 6000 |
| **Viscosity at 40°C** | mm2/s | 83,7 |
| **Viscosity at 100°C** | mm2/s | 14 |
| **Viscosity Index** | | 173 |
| **Flash point COC, °C** | °C | 232 |
| **Pour point, °C** | °C | -45 |
| **TBN Alcalinity** | mgKOH/g | 10,5 |
| **Sulphated Ash contents** | % | 1,33 |

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

## RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 36 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

## REFERENCES & AVAILABILITIES

| | |
|---|---|
| 36141 | 12 x 1 L |
| 36142 | 4 x 4 L |
| 36143 | 3 X 5 L |
| 36144 | 60 L |
| 36147 | 205 L |


SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers,3, ZI Tournai Ouest II
T: (+32) (0) 69 59 03 60
www.bardahl.be
www.bardahloils.com