# XTC 10W40

## DESCRIPTION

High performance, semi synthetic motor oil for petrol and diesel engines, turbo-charged or not. This engine oil is suitable for extended oil drain intervals. Excellent protection at cold start and at different temperatures.

## APPLICATION

**BARDAHL XTC 10w40** can be used all year long and in the most difficult operating conditions. Offers a good fluidity at low temperature.

## SPECIFICATIONS

This product offers the following performance level:

| | |
|---|---|
| ACEA | A3/B4 |
| API | SP / CF |
| BMW | Longlife-98 |
| VW | 501.01 / 505.00 |
| MB | 229.1 |

## PROPERTIES

- ✓ Offers a stable viscosity,
- ✓ Makes cold start easier,
- ✓ Provides a good resistance to oxidation.


SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers,3, ZI Tournai Ouest II
T: (+32) (0) 69 59 03 60
www.bardahl.be
www.bardahloils.com

## TECHNICAL DATA

| | | |
|---|---|---|
| **Density at 15°C** | Kg/l | 0,868 |
| **Viscosity at -25°C** | cP | 6500 |
| **Viscosity at 40°C** | mm2/s | 95 |
| **Viscosity at 100°C** | mm2/s | 14,2 |
| **Viscosity Index** | | 152 |
| **Pour point, °C** | °C | -39 |
| **TBN alcalinity** | mgKOH/g | 10,3 |
| **Sulphated ash contents** | % | 1,3 |

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

## RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

## REFERENCES & AVAILABILITIES

| | |
|---|---|
| 36241 | 12 x 1 L |
| 36242 | 4 x 4 L |
| 36243 | 3 x 5 L |
| 36248 | 20 L |
| 36244 | 60 L |
| 36247 | 205 L |


SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers,3, ZI Tournai Ouest II
T: (+32) (0) 69 59 03 60
www.bardahl.be
www.bardahloils.com