FICHE TECHNIQUE
V092026

XTEC 5W30 ST

DESCRIPTION

High viscosity index and ultra-high performance synthetic oil, which promotes fuel economy, formulated with the latest generation additives. It offers protection against low-speed pre-ignition (LSPI).

APPLICATION

BARDAHL XTEC 5w30 ST is based on technology that ensures excellent protection. BARDAHL 5w30 XTEC ST is suitable for both petrol (Euro 5 and 6) and diesel engines. It has a low ash content and is specially designed to reduce fuel consumption and CO2 emissions. Particularly suitable for DV5Rx and EB2 engines, it helps with camshaft maintenance. BARDAHL XTEC 5w30 ST is also compatible with petrol particulate filters (GPF) and biofuels.

SPECIFICATIONS

This product offers the following performance level:

ACEA	C3 - 23
API	SP/SQ
STELLANTIS	FPW9.55535/03 & /05
China	GB11121

PROPERTIES

✓ Prevents low-speed and low-revolution auto-ignition: Anti-LSPI (Low Speed Pre Ignition)
✓ High viscosity index (VI), very high viscosity stability especially at high temperatures
✓ Superior protection of the catalytic converter and DPF
✓ Fuel economy
✓ High resistance against oxidation
✓ Facilitates cold starts
✓ Anti-corrosion protection
✓ Very good detergency and dispersion

SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers,3, ZI Tournai Ouest II
T: (+32) (0) 69 59 03 60
www.bardahl.be
www.bardahloils.com

FICHE TECHNIQUE
V092026

TECHNICAL DATA

Density at 20°C	Kg/l	0,849
Viscosity at -30°C	mPa.s	5600
Viscosity at 40°C	mm2/s	69,1
Viscosity at 100°C	mm2/s	12,1
Viscosity Index		174
Flash point COC, °C	°C	234
Pour point, °C	°C	-45
HTHS	mPa.s	3,7

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling: any safety information related to the handling and use of this product are gathered in the Safety Data Sheet. Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

34951	12 x 1L
34953	3 x 5L
34954	60L
34957	205L
34958	20L
34959	1 000L

SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers,3, ZI Tournai Ouest II
T: (+32) (0) 69 59 03 60
www.bardahl.be
www.bardahloils.com