HF-S

DESCRIPTION

Very high performance synthetic hydraulic fluid with lubricating properties.

APPLICATION

BARDAHL HF-S is particularly suitable for hydraulic power steering systems, hydro-pneumatic suspensions, traction control systems, hydraulic for convertible roofs, centralized locking, etc. Do not use in transmissions. Do not use when a mineral fluid such as LHMPlus (fluorescent green color) is recommended.

SPECIFICATIONS

This product offers the following performance level:

DIN	51 524 Part 3
ISO	7308
FORD	M2C204-A
CHRYSLER	MS-11655B
MAN	M 3289
MERCEDES-BENZ	345.0
PSA	S71-2710
ZF	TE-ML-02K (ZF000832)
VW	TL-52.146 (G 002 000)
BENTLEY	JNV8622564F
BMW	8122 9 407758/ 8211 1 468041/ 8329 0 429576
FENDT	X 902 011 622
OPEL	B 040 0070 (Part N° 90 544 116)
PORSCHE	000 043 203 33
SAAB	3032 380
VOLVO	1161529

PROPERTIES

- ✓ Very high viscosity index for an excellent stability.
- ✓ Very low pour point.
- ✓ Very good anti-oxidation protection.

SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers,3, ZI Tournai Ouest II
T: (+32) (0) 69 59 03 60
www.bardahl.be
www.bardahloils.com

TECHNICAL DATA

Density at 20°C	Kg/m³	0,825
Viscosity 40°C	mm2/s	18,7
Viscosity 100°C	mm2/s	6
Viscosity at -40°C	mm2/s	1100
Viscosity index		313
Flash point COC, °C	°C	160
Pour point, °C	°C	-57
Colour		Dark green

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

36981	12 x 1 L

SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers,3, ZI Tournai Ouest II
T: (+32) (0) 69 59 03 60
www.bardahl.be
www.bardahloils.com