

Fuel treatment

Ref. 1069B

12x300ml

USE

Bardahl Fuel Treatment is a preventive product that can be used during the whole engine life. Its use is recommended to avoid the loss of power due to engine (petrol or diesel) clogging and wear.

Suitable for all types of petrol engines (injection, carburation, high pressure systems, Turbo-charging, LPG). Compatible with catalytic converters.

PROPERTIES

Thanks to its proprieties, Bardahl Fuel Treatment is effective to :

- Lubricate the upper part of cylinders and rings
- Prevent valves and seats from wear
- Prevent from pinking and auto-ignition
- Improve engine performances, power and responsiveness
- Disperse water from fuel
- Improve cold weather starts
- Limit fuel overconsumption
- Reduce exhaust fumes

INSTRUCTIONS FOR USE

Pour contents of the bottle into the tank before refueling.

PHYSICAL & CHEMICAL PROPERTIES

Color	Yellow
Physical state at 20°C	Liquid
Relative density	0,835-0,85 g/ml
Flash point	52°C
Kinematic viscosity	< 20 mm²/s

V08/2026

SADAPS BARDAHL CORPORATION S.A.
Rue de Lille, 104. 59420 MOUVAUX
T (+33) (0)3 10 38 38 38

SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue de Mont des Carliers, 3. ZI TOURNAI Ouest, 2
T: (+32) (0) 69 59 03 60

www.bardahl.be