DIESEL ANTI-BACTERIA BARDAHL

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Reference number: 1066B
Issue date: 11-07-18 Revision date: 17-03-23 Supersedes version of: 03-09-21 Version: 2.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : DIESEL ANTI-BACTERIA BARDAHL
UFI : YA53-68A4-MD90-DQ7J
Product code : 1066B # 733106R6
Type of product : Biocide regulation (EU 528/2012)

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Function or use category : Fuel additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Distributor
SADAPS BARDAHL Additives & Lubricants
ZI TOURNAI OUEST 2 - RUE DU MONT DES CARLIERS, 3
7522 TOURNAI
BELGIQUE
T +32 (0).69.59.03.60 - F +32 (0).69.59.03.61
msds@bardahlfrance.com - www.bardahl.be

Supplier
SADAPS BARDAHL Additives & Lubricants
ZI TOURNAI OUEST 2 - RUE DU MONT DES CARLIERS, 3
7522 TOURNAI
BELGIQUE
T +32 (0).69.59.03.60 - F +32 (0).69.59.03.61
msds@bardahlfrance.com - www.bardahl.be

1.4. Emergency telephone number

Emergency number : + 32 (0)70.245.245 / +33 (0)1.45.42.59.59

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals-24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital Msida MSD 2090 Msida	+356 2545 6508	
Saudi Arabia	Poison Control Center-Riyadh	General Directorate of Health Affairs Medial Province	+966 112324180 +966 112324189	
United Arab Emirates	Health Authority – Abu Dhabi (HAAD) Poison & Drug Information Center (PDIC)	P.O. Box 5674	+ 800-424	
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER	+44 20 7188 7188	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2	H225
Skin corrosion/irritation, Category 1, Sub-Category 1B	H314
Skin sensitisation, Category 1	H317
Germ cell mutagenicity, Category 2	H341
Carcinogenicity, Category 1B	H350
Aspiration hazard, Category 1	H304
Hazardous to the aquatic environment – Chronic Hazard, Category 3	H412

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02 GHS05 GHS07 GHS08

Signal word (CLP) : Danger

Contains : Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hazard statements (CLP) : H225 - Highly flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.
H314 - Causes severe skin burns and eye damage.
H317 - May cause an allergic skin reaction.
H341 - Suspected of causing genetic defects.
H350 - May cause cancer.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P201 - Obtain special instructions before use.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P260 - Do not breathe vapours.
P270 - Do not eat, drink or smoke when using this product.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, eye protection, face protection, protective clothing.
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER, a doctor.
P331 - Do NOT induce vomiting.
P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a POISON CENTER, a doctor.
P308+P313 - IF exposed or concerned: Get medical advice/attention.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P403+P235 - Store in a well-ventilated place. Keep cool.
P501 - Dispose of the empty packaging or the unused product in accordance with local regulations for waste disposal. In the second case, it is forbidden to recycle the packaging.

Extra phrases : Contains : 3,3′-methylenebis[5-methyloxazolidine] / Oxazolidine (CAS n° 66204-44-2) : 9,84g/100g, Protective agents used inside the containers, (TP6), Expiry date and batch number: see packaging, Immediate action, Not to be used for any purpose other than the one the product was designed for.
For professional users only.

2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics substance with national workplace exposure limit(s) (FR)	CAS-No.: 64742-48-9 EC-No.: 918-481-9 REACH-no: 01-2119457273-39	60-80	Asp. Tox. 1, H304 EUH066
isopropanol substance with national workplace exposure limit(s) (AT, BE, DE, DK, ES, FI, FR, GB, HU, IE, LV, PL, RO, SE)	CAS-No.: 67-63-0 EC-No.: 200-661-7 EC Index-No.: 603-117-00-0 REACH-no: 01-2119457558-25	15-30	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
3,3'-methylenebis[5-methyloxazolidine]	CAS-No.: 66204-44-2 EC-No.: 266-235-8	5-15	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 2, H341 Carc. 1B, H350 STOT RE 2, H373 Aquatic Chronic 2, H411 EUH071

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If medical advice is needed, have product container or label at hand.

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

First-aid measures after skin contact : Remove contaminated clothes. Wash skin with plenty of water. Wash contaminated clothing before reuse.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

First-aid measures after ingestion : Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact : Causes severe skin burns and eye damage. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Causes severe skin burns and eye damage.

Symptoms/effects after ingestion : May be fatal if swallowed and enters airways.
Chronic symptoms : Suspected of damaging fertility. May cause cancer.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Water spray. Dry powder. Foam.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour.
Hazardous decomposition products in case of fire : Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.
Other information : Prevent liquid from entering sewers, watercourses, underground or low areas.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area. Eliminate every possible source of ignition. Ensure adequate ventilation, especially in confined areas. Keep public away from danger area. Equip cleanup crew with proper protection.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Dike for recovery or absorb with appropriate material. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Recover the product with absorbent material.
Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Highly flammable liquid and vapour.
Precautions for safe handling : Do not eat, drink or smoke when using this product.
Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	:	Provide local exhaust or general room ventilation.
Storage conditions	:	Store in a closed container. Keep out of frost.
Heat and ignition sources	:	Keep away from naked flames/heat. Keep away from ignition sources.
Storage area	:	Store in a dry place. Store in a well-ventilated place.
Special rules on packaging	:	Store in original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

isopropanol (67-63-0)	
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	500 mg/m³
MAK (OEL TWA) [ppm]	200 ppm
MAK (OEL STEL)	2000 mg/m³
MAK (OEL STEL) [ppm]	800 ppm
Belgium - Occupational Exposure Limits	
Local name	Alcool isopropylique # Isopropylalcohol
OEL TWA	500 mg/m³
OEL TWA [ppm]	200 ppm
OEL STEL	1000 mg/m³
OEL STEL [ppm]	400 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 21/01/2020
Denmark - Occupational Exposure Limits	
OEL TWA [1]	490 mg/m³
OEL TWA [2]	200 ppm
OEL STEL	980 mg/m³
OEL STEL [ppm]	400 ppm
Finland - Occupational Exposure Limits	
HTP (OEL TWA) [1]	500 mg/m³
HTP (OEL TWA) [2]	200 ppm
HTP (OEL STEL)	620 mg/m³
HTP (OEL STEL) [ppm]	250 ppm
France - Occupational Exposure Limits	
Local name	Alcool isopropylique
VLE (OEL C/STEL)	980 mg/m³
VLE (OEL C/STEL) [ppm]	400 ppm
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)

isopropanol (67-63-0)	
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	500 mg/m³
AGW (OEL TWA) [2]	200 ppm
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	500 mg/m³
CK (OEL STEL)	2000 mg/m³
Ireland - Occupational Exposure Limits	
OEL TWA [2]	200 ppm
OEL STEL [ppm]	400 ppm
Latvia - Occupational Exposure Limits	
OEL TWA	350 mg/m³
OEL STEL	600 mg/m³
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	900 mg/m³
NDSCh (OEL STEL)	1200 mg/m³
Romania - Occupational Exposure Limits	
OEL TWA	200 mg/m³
OEL TWA [ppm]	81 ppm
OEL STEL	500 mg/m³
OEL STEL [ppm]	203 ppm
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [1]	500 mg/m³
VLA-ED (OEL TWA) [2]	200 ppm
VLA-EC (OEL STEL)	1000 mg/m³
VLA-EC (OEL STEL) [ppm]	400 ppm
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	350 mg/m³
NGV (OEL TWA) [ppm]	150 ppm
KTV (OEL STEL)	600 mg/m³
KTV (OEL STEL) [ppm]	250 ppm
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	999 mg/m³
WEL TWA (OEL TWA) [2]	400 ppm
WEL STEL (OEL STEL)	1250 mg/m³
WEL STEL (OEL STEL) [ppm]	500 ppm
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA) [1]	500 mg/m³
MAK (OEL TWA) [2]	200 ppm
KZGW (OEL STEL)	1000 mg/m³

isopropanol (67-63-0)	
KZGW (OEL STEL) [ppm]	400 ppm
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	980 mg/m³
ACGIH OEL TWA [ppm]	400 ppm

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)	
France - Occupational Exposure Limits	
VME (OEL TWA)	1200 mg/m³
VME (OEL TWA) [ppm]	184 ppm
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA) [1]	275 mg/m³
Grenseverdi (OEL TWA) [2]	50 ppm

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:
Safety glasses. ISO 16321-1

8.2.2.2. Skin protection

Skin and body protection:
Wear suitable protective clothing

Hand protection:
Gloves. ISO 374-1

Hand protection					
Type	**Material**	**Permeation**	**Thickness (mm)**	**Penetration**	**Standard**
Gloves	Nitrile rubber (NBR)	5 (> 240 minutes), 6 (> 480 minutes)	>0.35	3 (> 0.65)	EN ISO 374, EN 388, EN 407

8.2.2.3. Respiratory protection

Respiratory protection:
Good ventilation of the workplace required. Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Colour	:	Colourless.
Appearance	:	clear.
Odour	:	Not available
Odour threshold	:	Not available
Melting point	:	Not available
Freezing point	:	Not available
Boiling point	:	> 35 °C
Flammability	:	Not available
Explosive limits	:	Not available
Lower explosion limit	:	Not available
Upper explosion limit	:	Not available
Flash point	:	16 °C
Auto-ignition temperature	:	Not available
Decomposition temperature	:	Not available
pH	:	Not available
Viscosity, kinematic	:	< 20,5 mm²/s (40°C)
Solubility	:	Not available
Partition coefficient n-octanol/water (Log Kow)	:	Not available
Vapour pressure	:	Not available
Vapour pressure at 50°C	:	Not available
Density	:	0,805 g/cm³ (20°C)
Relative density	:	Not available
Relative vapour density at 20°C	:	Not available
Particle characteristics	:	Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Heat. Open flame. Sparks. Water, humidity. Freezing.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

isopropanol (67-63-0)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 ml/kg
LC50 Inhalation - Rat [ppm]	> 10000 ppm (6hours)

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 Inhalation - Rat	4951 mg/m³ 4 hours

Skin corrosion/irritation : Causes severe skin burns.
Serious eye damage/irritation : Assumed to cause serious eye damage
Respiratory or skin sensitisation : May cause an allergic skin reaction.
Germ cell mutagenicity : Suspected of causing genetic defects.
Carcinogenicity : May cause cancer.
Reproductive toxicity : Not classified
STOT-single exposure : Not classified

isopropanol (67-63-0)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

3,3'-methylenebis[5-methyloxazolidine] (66204-44-2)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : May be fatal if swallowed and enters airways.

DIESEL ANTI-BACTERIA BARDAHL	
Viscosity, kinematic	< 20,5 mm²/s (40°C)

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)	
Viscosity, kinematic	1,3 mm²/s

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short–term (acute) : Not classified

Hazardous to the aquatic environment, long–term (chronic) : Harmful to aquatic life with long lasting effects.

isopropanol (67-63-0)	
LC50 - Fish [1]	4200 mg/l (rasbora heteromorpha)
EC50 - Crustacea [1]	> 100 mg/l (Daphnia magna)
EC50 - Crustacea [2]	1400 – 1950 mg/l (Crangon crangon)
EC50 72h - Algae [1]	> 100 mg/l (Scenedesmus subspicatus)

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)	
LC50 - Fish [1]	> 1000 mg/l
EC50 - Crustacea [1]	> 1000 mg/l Daphnia Magna
EC50 72h - Algae [1]	> 1000 mg/l Pseudokirchnerella subcapitata
NOEC chronic algae	1000 mg/l Pseudokirchnerella subcapitata

3,3'-methylenebis[5-methyloxazolidine] (66204-44-2)	
LC50 - Fish [1]	57,7 mg/l
LC50 - Fish [2]	71 mg/l
EC50 - Crustacea [1]	37,9 mg/l (Daphnia magna)
EC50 - Crustacea [2]	28 mg/l (Daphnia magna)
EC50 72h - Algae [1]	5,7 mg/l
NOEC chronic crustacea	1,3 mg/l
NOEC chronic algae	2,2 mg/l

12.2. Persistence and degradability

isopropanol (67-63-0)	
Persistence and degradability	Readily biodegradable.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)	
Biodegradation	80 % 28 days

3,3'-methylenebis[5-methyloxazolidine] (66204-44-2)	
Biodegradation	69 % (OECD TG 301 D), 89.9% (OECD TG 301 B)

12.3. Bioaccumulative potential

isopropanol (67-63-0)	
Bioaccumulative potential	not bioaccumulable.

3,3'-methylenebis[5-methyloxazolidine] (66204-44-2)	
Partition coefficient n-octanol/water (Log Kow)	-0,389

12.4. Mobility in soil

isopropanol (67-63-0)	
Ecology - soil	In water, material soluble.

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Sewage disposal recommendations : Do not discharge into drains or the environment.

Product/Packaging disposal recommendations : Collect all waste in suitable and labelled containers and dispose according to local legislation.

Additional information : Empty the packaging completely prior to disposal. Do not re-use empty containers.

Ecology - waste materials : Do not discharge the product into the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID

ADR	IMDG	IATA	RID
14.1. UN number or ID number			
UN 2924	UN 2924	UN 2924	UN 2924
14.2. UN proper shipping name			
FLAMMABLE LIQUID, CORROSIVE, N.O.S.	FLAMMABLE LIQUID, CORROSIVE, N.O.S.	Flammable liquid, corrosive, n.o.s.	FLAMMABLE LIQUID, CORROSIVE, N.O.S.
Transport document description			
UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S. (CONTAINS : isopropanol ; 3,3'-methylenebis[5-methyloxazolidine]), 3 (8), II, (D/E)	UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S. (CONTAINS : isopropanol ; 3,3'-methylenebis[5-methyloxazolidine]), 3 (8), II	UN 2924 Flammable liquid, corrosive, n.o.s. (CONTAINS : isopropanol ; 3,3'-methylenebis[5-methyloxazolidine]), 3 (8), II	UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S. (CONTAINS : isopropanol ; 3,3'-methylenebis[5-methyloxazolidine]), 3 (8), II
14.3. Transport hazard class(es)			
3 (8)	3 (8)	3 (8)	3 (8)
			
14.4. Packing group			
II	II	II	II

ADR	IMDG	IATA	RID
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available			

14.6. Special precautions for user

Overland transport

Classification code (ADR)	:	FC
Special provisions (ADR)	:	274
Limited quantities (ADR)	:	1l
Excepted quantities (ADR)	:	E2
Packing instructions (ADR)	:	P001, IBC02
Mixed packing provisions (ADR)	:	MP19
Portable tank and bulk container instructions (ADR)	:	T11
Portable tank and bulk container special provisions (ADR)	:	TP2, TP27
Tank code (ADR)	:	L4BH
Vehicle for tank carriage	:	FL
Transport category (ADR)	:	2
Special provisions for carriage - Operation (ADR)	:	S2, S20
Hazard identification number (Kemler No.)	:	338
Orange plates	:	
Tunnel restriction code (ADR)	:	D/E
EAC code	:	•3WE
APP code	:	A(fl)

Transport by sea

Special provisions (IMDG)	:	274
Packing instructions (IMDG)	:	P001
IBC packing instructions (IMDG)	:	IBC02
Tank instructions (IMDG)	:	T11
Tank special provisions (IMDG)	:	TP2, TP27
EmS-No. (Fire)	:	F-E
EmS-No. (Spillage)	:	S-C
Stowage category (IMDG)	:	B
Stowage and handling (IMDG)	:	SW2
Properties and observations (IMDG)	:	Causes burns to skin, eyes and mucous membranes.

Air transport

PCA Excepted quantities (IATA)	:	E2
PCA Limited quantities (IATA)	:	Y340
PCA limited quantity max net quantity (IATA)	:	0.5L
PCA packing instructions (IATA)	:	352
PCA max net quantity (IATA)	:	1L
CAO packing instructions (IATA)	:	363
CAO max net quantity (IATA)	:	5L
Special provisions (IATA)	:	A3, A803
ERG code (IATA)	:	3CH

Rail transport

Classification code (RID)	:	FC
Special provisions (RID)	:	274
Limited quantities (RID)	:	1L
Excepted quantities (RID)	:	E2

Packing instructions (RID)	:	P001, IBC02
Mixed packing provisions (RID)	:	MP19
Portable tank and bulk container instructions (RID)	:	T11
Portable tank and bulk container special provisions (RID)	:	TP2, TP27
Tank codes for RID tanks (RID)	:	L4BH
Transport category (RID)	:	2
Colis express (express parcels) (RID)	:	CE7
Hazard identification number (RID)	:	338

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Seveso Directive (Disaster Risk Reduction)

Seveso III Part I (Categories of dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
P5c FLAMMABLE LIQUIDS Flammable liquids, Categories 2 or 3 not covered by P5a and P5b	5000	50000

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 49	Skin disorders caused by aliphatic, alicyclic amines or ethanolamines
RG 65	Eczematiform lesions of allergic mechanism
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG). Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1).

Chemicals Prohibition Ordinance (ChemVerbotsV) : This product is subject to ChemVerbotsV Annex 2 Entry 1. The following requirements must be observed: authorization requirement (according to § 6 paragraph 1 sentence 1), basic requirements for carrying out the delivery (according to § 8 paragraph 1, 3 and 4), identification and documentation (according to § 9 paragraph 1 to 3) and exclusion of the shipping route (according to § 10).

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen : 3,3'-methylenebis[5-methyloxazolidine] is listed

SZW-lijst van mutagene stoffen : 3,3'-methylenebis[5-methyloxazolidine] is listed

SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed

SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed

SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Class for fire hazard : Class I-1

Store unit : 1 liter

Classification remarks : F <Flam. Liq. 2>; Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

Switzerland

Storage class (LK) : LK 3 - Flammable liquids

Chemicals Ordinance (SR 813.11) : Group 1

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4

Full text of H- and EUH-statements:	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1B	Carcinogenicity, Category 1B
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Muta. 2	Germ cell mutagenicity, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.